<u>т</u>	۵	н г	m			0	Ξ	Þ	
	Z	ØS							
)						LAYOUT SHOWN AS E	XAMPLE		
		Keying Show	vn as example						
CHARACTERISTICS			Connector dimension	_					
-Standard : Based on MI	L-DTL-38999 Series III		Dim Nominal						
-Shell Plating -Insulator	Z 31 Max Plating : Black Zinc Nickel tor : Thermoplastic VV THREAD M22x1-6g tor : Thermoplastic (professional recommendation, technical notice.)								
	: Silicon Elastomer					Count		& Control List	
-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles					FR Not Listed PN: 8D515Z05SC				
-Delivered with Souriau	contacts and Accessories					PN: 80515	20530		
	-65°C to +175°C				A 19-10-2016	First Release			
	: 500 hours : 31.38 g ± 10%				ISS DATE	Latest modification - by			MOD N°
	· 31.30 ξ ± 10/0				Designed By:	Date:	CUS	TOMER DRAWING	
					TITLE	Alumir	nium Plug 8D se	ries	
BASIC SERIES:	8D 5 - 15	Z 05 S C	I		SCALE	General linear	N	IPRDS / PROJECT	
SHELL TYPE : Plug with					NA -	Tolerances:		859	
			<u>ــــــــــــــــــــــــــــــــــــ</u>	RIENTATION : C				This document is the proper SOURIAU	rty of
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 15 CONTACT TYPE : SOCKET(500 Matings)					SOURIAU WWW.SOURIAU.COM it must not be reproduced or communicated without permissi				
PLATING : $Z = B$	ack Zinc Nickel	· · · · · ·		LAYOUT : 15-05	FORMAT	SOURIAU			SHEET
		I	conner		A3	8D515Z			1/2

	T	G	г	m		0
4		Contact Layout $ \begin{array}{c} & & & \\ & & \\$				
		X-axis (mm) Y-axis (mm) +.000 (0.00) +.100 (2.54) +.174 (4.42) +.024 (0.61) +.094 (2.39) 148 (3.76) 094 (2.39) 148 (3.76) 174 (4.42) +.024 (0.61)				
ω						
						SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda
N						Count FR
						PN: 8D515
					A 19-10-20 ISS DATE	116 First Release
					Designed By:	Date:
					TITLE	Alumii
<u> </u>					SCALE NA	General linear Tolerances: ±
					SOURIA	U WWW.SOURIAU.
					FORMAT	SOURIAL
		<u></u>		r (A3	8D515Z
	Н	G	l F	E \	D	C

