

External Antenna - Connector Mount

WXE

Innovative **Technology** for a **Connected** World



WXE2400


Today's work and lifestyles require us to communicate anytime, anywhere whether on the move or sitting still. Bluetooth and 802.11 standards make wireless connections to computer networks and other devices possible, while at the same time enabling freedom of movement.

Laird Technologies' practical and rugged external wireless device antennas are designed to fit into the portable devices used in office, industrial and home environments. The antennas feature flexible elements and many are ½ wave coaxial dipole design for reduced ground dependence and improved performance.

FEATURES

- Injection molded high performance flexible cable antenna
- ½ wave coaxial dipole design for improved performance
- FCC Part 15 compliant connector

PARAMETER	SPECIFICATION	
Frequency	2.4 - 2.5 GHz	
VSWR	2:1 max at resonance	
Polarization	Vertical	
Gain	3.0 dBi	
Nominal Impedance	50 ohms	
Power Rating	50 watts	
Temperature	-40° to +850°C	
Length	5.5"	
Drop Test	1M	



CONNECTORS		
MODEL#	PART#	CONNECTOR
WXE2400-SM	CAF29155	SMA-Male flush
WXE2400-SMLH	CAF28832	SMLH-Male flush

global solutions: local support ™

Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12 IAS-EUSales@lairdtech.com Asia: +1.65.6.243.8022 IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-WXE 0809

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies in the Technologies and the Technologies and the Technologies and the Technologies of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies from an expension of the Technologies from the Te