

DETAILS


Product Number	C13297_SATU-O
Family	Satu
Type	Lens array
Color	clear
Diameter	21,8 mm
Height	8,9 mm
Style	round
Optic Material	PMMA
Holder Material	
Fastening	glue, pin
Status	production ready
ROHS Compliant	Yes
Date Updated	6/05/2014




OPTICAL PROPERTIES

LED	Viewing	Light	Effi-		Connector
	Angle	Beam	ciency	cd/lm	
XT-E	sim: 20+40	Oval	-	-	-
XP-E2	40+17 deg	Oval	85 %	3.000	-
XP-G2	39+24 deg	Oval	84 %	2.200	-
XB-D	42+22 deg	Oval	77 %	2.000	-
XP-E	41+17 deg	Oval	83 %	2.900	-
XP-G	39+23 deg	Oval	79 %	2.200	-
H35B0 (LEMWA32)	39+24 deg	Oval	84 %	2.200	-
H35C0 (LEMWA33)	39+25 deg	Oval	82 %	2.000	-
LUXEON T	40+24 deg	Oval	84 %	2.000	-
LUXEON H50-2	sim: 22+42	Oval	sim: 85 %	sim: 2.000	-
LUXEON TX	40+25 deg	Oval	79 %	1.900	-
NF2x757A	43+26 deg	Oval	81 %	1.500	-
NVSxx19B/NVSxx19C	sim: 43+24	Oval	sim: 82 %	sim: 1.950	-
Oslon Square EC	41+23 deg	Oval	82 %	2.000	-
Oslon SSL 80	41+18 deg	Oval	79 %	2.500	-
Synios P2720 1/2 mm	sim: 25+12	Oval	sim: 91 %	sim: 3.450	-
LH351Z	40+23 deg	Oval	84 %	2.300	-
Z8Y22P	sim: 43+26	Oval	sim: 80 %	sim: 1.710	-


Relative intensity of C13297_SATU-O_(XB-D)




Relative intensity of C13297_SATU-O_(XP-E)



Relative intensity of C13297_SATU-O_(XP-G)



Relative intensity of C13297_SATU-O_(SSL80)






D

C

B

A




INDEX	PART NO	DESCRIPTION	MATERIAL	COLOUR
1	C13297	SATU-0	PMMA	

Tolerances if not otherwise shown
According to DIN ISO 2768-1
Linear measures:
Up to 30mm class M, otherwise class C.
According to DIN ISO 2768-2
Form and position: class L

LEDiL

Ledil Oy
Salorankatu 10
FIN 24240 SALO
Finland

THIRD ANGLE PROJECTION:



DRAWING TITLE

C13297_SATU-0

This drawing is the property
of LEDiL Oy. It may not be
reproduced, copied or
communicated without a written
agreement with LEDiL Oy."

SIZE PART NUMBER

A4


C13297

SCALE	2:1	WEIGHT	2 g	SHEET	1/1
-------	-----	--------	-----	-------	-----

D


A

Luminaire: Ledil Oy C13297_SATU-O_(XP-E2) Efficiency=85%
Lamps: 1 x CREE XP-E2 (XP-E2) 243lm@250mA CCT=3200K P=2.2W I=250mA




Luminaire: Ledil Oy C13297_SATU-O_(XP-G2) Efficiency=84%


Lamps: 1 x CREE XP-G2 (XPGBWT-L1-000-00G51) 303lm@250mA CCT=7000K P=2.2W I=250mA




Luminaire: Ledil Oy C13297_SATU-O_(3535_2W) Efficiency=84%
Lamps: 1 x LG 3535 Ceramic 2W (LEMWA32) 192lm@250mA CCT=7700k P=2.2W I=250mA




Luminaire: Ledil Oy C13297_SATU-O_(3535_3W) Efficiency=82%
Lamps: 1 x LG 3535 Ceramic 3W (LEMWA33) 278lm@250mA CCT=6287K P=2.2W I=250mA




Luminaire: LEDiL Oy C13297_SATU-O_(LUXEON_T)_1 Eff.84%
Lamps: 1 x LUXEON_T (211lm@250mA)




Luminaire: Ledil Oy C13297_SATU-O_(Luxeon_TX) Efficiency=79%
Lamps: 1 x Luxeon TX 250lm @ 250mA CCT= P=2.13 I=250mA



Luminaire: LEDil Oy C13297_SATU-O_(NF2x757A) Efficiency=81%
Lamps: 1 x Nichia NF2x757A (NF2W757ART) 197lm @ 100mA CCT=4700K P=1.9W I=100mA




Luminaire: Ledil oy C13297_SATU-O (Osram Square EC 273lm @ 250mA) Efficiency=82%
Lamps: 1 x Osram Square EC (LCW CQAR.EC-MQMS-SL7N-35) 273lm @ 250mA CCT=3955K P=2,25W I=250mA




Luminaire: LEDil Oy C13297_SATU-O_(LH351Z)

Lamps: 1 x Samsung LH351Z (234.33lm @ 250mA) CCT=6500K P=2.2W I=250mA




Luminaire: Ledil Oy C13297_SATU-O_SEOUL_Z8Y22+_SIMULATED
Lamps: 1 x SEOUL Z8Y22 Plus



Luminaire: Ledil Oy C13297_SATU-O_(XP-E2) Efficiency=85%


Lamps: 1 x CREE XP-E2 (XPEBWT-L1-0000-00CE7) 243lm@250mA CCT=3200K P=2.2W I=250mA



cd/klm

— C0 - C180 — C90 - C270

Luminaire: Ledil Oy C13297_SATU-O_(XP-G2) Efficiency=84%
Lamps: 1 x CREE XP-G2 (XPGBWT-L1-000-00G51) 303lm@250mA CCT=7000K P=2.2W I=250mA




cd/klm

— C0 - C180

— C90 - C270


Luminaire: Ledil Oy C13297_SATU-O_(3535_2W) Efficiency=84%
Lamps: 1 x LG 3535 Ceramic 2W (LEMWA32) 192lm@250mA CCT=7700k P=2.2W I=250mA



cd/klm
— C0 - C180 — C90 - C270

Luminaire: Ledil Oy C13297_SATU-O_(3535_3W) Efficiency=82%

Lamps: 1 x LG 3535 Ceramic 3W (LEMWA33) 278lm@250mA CCT=6287K P=2.2W I=250mA




cd/klm


— C0 - C180

— C90 - C270


Luminaire: LEDiL Oy C13297_SATU-O_(LUXEON_T)_1 Eff.84%
Lamps: 1 x LUXEON_T (211lm@250mA)



Luminaire: Ledil Oy C13297_SATU-O_(Luxeon_TX) Efficiency=79%
Lamps: 1 x Luxeon TX 250lm @ 250mA CCT= P=2.13 I=250mA




Luminaire: LEDil Oy C13297_SATU-O_(NF2x757A) Efficiency=81%
Lamps: 1 x Nichia NF2x757A (NF2W757ART) 197lm @ 100mA CCT=4700K P=1.9W I=100mA



cd/klm

— C0 - C180 — C90 - C270

Luminaire: Ledil oy C13297_SATU-O (Osram Square EC 273lm @ 250mA) Efficiency=82%
Lamps: 1 x Osram Square EC (LCW CQAR.EC-MQMS-SL7N-35) 273lm @ 250mA CCT=3955K P=2,25W I=250mA




cd/klm

— C0 - C180 — C90 - C270

Luminaire: LEDil Oy C13297_SATU-O_(LH351Z)

Lamps: 1 x Samsung LH351Z (234.33lm @ 250mA) CCT=6500K P=2.2W I=250mA




cd/klm

— C0 - C180

— C90 - C270

Luminaire: Ledil Oy C13297_SATU-O_SEOUL_Z8Y22+_SIMULATED
Lamps: 1 x SEOUL Z8Y22 Plus



cd/klm

— C0 - C180

— C90 - C270

η = 80%

NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.