



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. CONTACT MATERIAL: COPPER ALLOY W/ SILVER PLATE
5. RATING: 7A@125V, 4A@250
6. CONTACT RESISTANCE: 20MΩ MAX @ 5V DC 1A
7. DIELECTRIC STRENGTH: AC 1500V RMS
8. OPERATING FORCE: 550±150gf TYP.
9. TRAVEL: FULL:5.5, LOCK:4.0
10. ▲ DENOTES CRITICAL PARAMETER.

|      |  |         |                         |        |      |       |        |                    |         |     |
|------|--|---------|-------------------------|--------|------|-------|--------|--------------------|---------|-----|
| A    |  | 13123   | RELEASED FOR PRODUCTION | 5/9/03 | AR   | TITLE |        | P227EE1A20B.094BLK |         |     |
| REV. |  | ECN No. | DESCRIPTION             | DATE   | CHKD | SCALE | DATE   | DR                 | DWG     | REV |
|      |  |         |                         |        |      | 1.5:1 | 5/9/03 | AR                 | XP0257A | A   |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

