



| Shellsize | A | B | C | D | E | F ⁺¹ ₋₃ | G | Cable ϕ | Part-NO. |
|-----------|-------|-------|-------|------|------|-------------------------------|------|--------------|------------|
| 1 | 40.76 | 25.00 | SW 20 | 51.0 | 22.0 | 77.0 | 44.0 | 5 - 10 | 165X15319X |
| 2 | 49.06 | 33.30 | SW 24 | 51.0 | 22.0 | 79.0 | 52.0 | 7 - 12 | 165X15329X |
| 3 | 62.80 | 47.04 | SW 24 | 59.5 | 22.0 | 87.5 | 52.0 | 7 - 12 | 165X15339X |
| 4 | 78.86 | 63.50 | SW 30 | 67.0 | 22.0 | 99.0 | 52.0 | 9 - 16 | 165X15349X |
| 5 | 76.46 | 61.10 | SW 40 | 67.0 | 24.8 | 107.0 | 52.0 | 13 - 20 | 165X15359X |

Directive 2002/95 EC
„RoHS“
Compliant

- NOTES:**
- HOOD: ABS V0, METALLIZED
 - SCREWS: STAINLESS STEEL

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

CUSTOMER APPROVAL DATE:

NAME: TITLE:

COMPANY NAME:

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

| | | | |
|-------|-------------|------------|--------|
| 2 x b | Ä 3353 | 29.04.2009 | Lehmen |
| a | Origin | | |
| rev. | description | date | name |

| | | | |
|-----------|------------|--------------------|--|
| tolerance | dim. in mm | scale: 1:1 | material: SEE NOTES |
| 2004 | date | name | title: WATER RESISTANT D-SUB HOOD 9-50pos. with jack screw |
| drawn | 15.08. | Lehmenkühler | |
| appd. | 15.08. | Kühle | |
| norm | | | dwg no: AutoCAD 2004 DIN-A 3 sh: 1/1 |
| d-old | | | |
| CONEC® | | part no: SEE TABLE | |