ב ביו ביו ביו ביו ביו ביו ביו ביו ביו בי			0	σ		
Z Z D D D D D D D D D D D D D D D D D D						
	Keying Shown as example		LAYOUT SHOWN	A AS EXAMPLE		
CHARACTERISTICS	Connector dimensio					
-Standard : Based on MIL-DTL-38999 Series III	Dim Non   ØS 41.7					7
-Shell Material : Aluminium -Shell Plating : Nickel	Z 311 VV THREAD M31		SOURIAU shall not be liable f due to a use of the Produc	for any non-conformity or d cts which does not comply		
-Insulator : Thermoplastic		-0	the Specifications issued by eit	her of the Parties or by a th	nird party	
-Contacts : Copper Alloy			(proressional recomm	endation, technical notice.	1	
-Seals & Grommet : Silicon Elastomer			C		& Control List : Listed	
-Contact Plating: Gold over copper Alloy 0.8μm minimum-Durability: 500 Mating cycles				IN NOT		
-Delivered with Souriau contacts and Accessories			PN: 8D5	21F39PN		
-Temperature Range65°C to +200°C						
-Salt Spray : 48 hours		A 06-10	-2016 First Release			
Mass : 44.27 g ± 10%		ISS DA Designed By:	TE Latest modification - by Date:			MOD N°
		TITLE		iminium Plug 8D se		
	39 P N	SCALE	General lir Tolerance	-	NPRDS / PROJECT <b>859</b>	
SHELL TYPE : Plug with RFI Shielding		NA			This document is the property	y of
CONTACT TYPE : Standard Crimp Contact		ORIENTATION : N SOURI	AU WWW.SOURIA		SOURIAU it must not be reproduced o	
SHELL SIZE : 21		E : PIN(500 Matings)			communicated without permis	
PLATING : F = Nickel	CONT	ACT LAYOUT : 21-39		AU DRG N° 1F39PN-C		SHEET 1/2

