



## Screwless Connectors Block Connectors

### 930-00/ 2

terminal block without release keys, 2 pole, voltage rating: 450 V,  
current rating: 24 A, cross-section rating: 2.5 mm<sup>2</sup>



### Order Info

<b>reference number (ref. no.)</b>	112002
<b>Applications</b>	Lighting, Electrical Appliances
<b>PU</b>	1,000
<b>EAN</b>	4028012100255

### Type

<b>type</b>	terminal block without release keys
<b>number of poles</b>	2 pole
<b>clamping units per pole</b>	2
<b>colour</b>	white
<b>cross-section rating</b>	2.5 mm <sup>2</sup>

### Technical Data

<b>voltage rating</b>	450 V
<b>current rating</b>	24 A
<b>insulating material</b>	PA 6.6
<b>contact material</b>	brass
<b>flammability rating</b>	V-2
<b>max. Ambient Temperature Operation</b>	85 °C
<b>stripping length</b>	8.0-9.0 mm
<b>internal core cross-section max.</b>	2.5 mm <sup>2</sup>
<b>external core cross-section min.</b>	0.5 mm <sup>2</sup>
<b>external core cross-section max.</b>	2.5 mm <sup>2</sup>
<b>internal core cross-section min.</b>	0.5 mm <sup>2</sup>
<b>Type of Conductor Solid External</b>	yes
<b>Type of Conductor Solid Internal</b>	yes
<b>Approbation EN60998</b>	930_935_937_EN60998_20071001_VDE_40022275_web.pdf
<b>Approbation UL</b>	930_935_19880415_19941222_UL_E63492_1-06_Description_web.
<b>Approbation CSA</b>	Schraub_Steck_Schraubenlos_SI_Klemmen_20160429_CSA_700765