



Screwless Connectors Block Connectors

930-02/ 4

terminal block with 2 release keys, 4 pole, voltage rating: 450 V, current rating: 24 A, cross-section rating: 2.5 mm²



Order Info

reference number (ref. no.)	112404
Applications	Lighting, Electrical Appliances
PU	500
EAN	4028012103782

Type

type	terminal block with 2 release keys
number of poles	4 pole
clamping units per pole	2
colour	white
cross-section rating	2.5 mm ²

Technical Data

voltage rating	450 V
current rating	24 A
insulating material	PA 6.6
contact material	brass
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
stripping length	8.0-9.0 mm
internal core cross-section max.	2.5 mm ²
external core cross-section min.	0.5 mm ²
external core cross-section max.	2.5 mm ²
internal core cross-section min.	0.5 mm ²
Type of Conductor Solid External	yes
Type of Conductor Solid Internal	yes
Approbation EN60998	930_935_937_EN60998_20071001_VDE_40022275_web.pdf
Approbation UL	930_935_19880415_19941222_UL_E63492_1-06_Description_web.
Approbation CSA	Schraub_Steck_Schraubenlos_SI_Klemmen_20160429_CSA_700765