



Screw Terminal Blocks

230 K/ 2

terminal block, 2 pole, insulating material: PA 6, cross-section rating: 2.5 mm², pin spacing: 8.0 mm, fixing: screw, voltage rating: 450 V, current rating: 24 A



Order Info

reference number (ref. no.)	121602
Applications	Lighting, Installation, Electrical Appliances
PU	2,000
EAN	4028012105298

Type

type	terminal block
number of poles	2 pole
clamping units per pole	1
colour	natural
cross-section rating	2.5 mm ²

Technical Data

voltage rating	450 V
current rating	24 A
insulating material	PA 6
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	4.0 mm ²
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	5.0-5.5 mm
Assembly Contact Screw	0.8x4.0 / ⌀ 0.5 Nm
pin spacing	8.0 mm
fixing	screw
Approbation EN60998	200_230_EN60998_20012012_VDE_ENEC_40034813_web.pdf
Approbation UL	230_19820924_20120103_UL_E63492_1-02_Description_web.pdf
Approbation CSA	Schraub_Steck_Schraubenlos_SI_Klemmen_20160429_CSA_700765

Accessories

230 BZ/ 2	191202
ZEL 110	196420
