



Connectors System AC 166®  
Distributor

AC 166 GVT 3/ 3 black

T-Form 1 input terminal/2 output terminals, 3 pole, black, coding: 1 (mains), voltage rating: 250 V, current rating: 20 A



Order Info

<b>reference number (ref. no.)</b>	167163
<b>Applications</b>	Lighting, Installation
<b>PU</b>	100
<b>EAN</b>	4028012102167

Type

<b>type</b>	T-Form 1 input terminal/2 output terminals
<b>number of poles</b>	3 pole
<b>colour</b>	black
<b>coding</b>	1 (mains)
<b>PE function</b>	yes
<b>protection against incorrect plugging</b>	yes
<b>latch</b>	yes

Technical Data

<b>voltage rating</b>	250 V
<b>current rating</b>	20 A
<b>insulating material</b>	PA 6.6
<b>contact material</b>	brass
<b>impulse voltage rating</b>	4.0 kV
<b>flammability rating</b>	V-2
<b>max. Ambient Temperature Operation</b>	100 °C
<b>IP code</b>	IP20
<b>IP code when plugged</b>	IP40
<b>Approbation EN61535</b>	AC166-G_Leitungen_EN61535_20121212_20180725_VDE_ENEC_4C
<b>Approbation UL</b>	160_163_AC164_AC166_20011003_20170727_UL_E220480_Sec.1-(