



## Fused Terminal Blocks

### 503 Si/ 2 DS GW

screwklemme, 2 pole, wire protector (DS): yes, cross-section rating: 2.5 mm<sup>2</sup>, voltage rating: 400 V, current rating: 10 A



## Order Info

reference number (ref. no.)	1703G2
Applications	Lighting, Electrical Appliances, Transformers, Electronics
PU	300
EAN	4028012117956

## Type

type	screwklemme
number of poles	2 pole
clamping units per pole	1
colour	natural
cross-section rating	2.5 mm <sup>2</sup>
wire protector (DS)	yes

## Technical Data

voltage rating	400 V
current rating	10 A
insulating material	PA 6.6-GW
contact material	brass
core cross-section min.	0.5 mm <sup>2</sup>
core cross-section max.	2.5 mm <sup>2</sup>
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.0-7.5 mm
Assembly Contact Screw	0.8x4.0 / ⚙ 0.5 Nm
mounting hole diameter	3.1 mm
Type of Conductor Solid External	yes
Type of Conductor Flexible External	yes
Type of Conductor Stranded External	yes
Type of Conductor Solid Internal	yes

<b>Type of Conductor Stranded Internal</b>	yes
<b>Type of Conductor Flexible Internal</b>	yes
<b>Approbation EN60127</b>	503Si_EN60127_20011122_20170509_VDE_HA139514_web.pdf
<b>Approbation UL</b>	503Si_1003Si_19961021_20100409_UL_E63492_1-14_Description_
<b>Approbation CSA</b>	Schraub Steck Schraubenlos SI Klemme_20160429_CSA_70076573_Report_web.pdf

## Accessories

<b>ZEL 110</b>	196420
----------------	--------