



## SMD Connectors

### SMDflat 345/ 2 white

terminal block, pin spacing: 4.0 mm, 2 pole, current rating: 6 A, voltage rating: 250 V



## Order Info

<b>reference number (ref. no.)</b>	351102
<b>Applications</b>	Lighting
<b>PU</b>	1,500 (tape-on-reel)
<b>EAN</b>	4028012112456

## Type

<b>type</b>	terminal block
<b>number of poles</b>	2 pole
<b>clamping units per pole</b>	1
<b>colour</b>	white

## Technical Data

<b>voltage rating</b>	250 V
<b>current rating</b>	6 A
<b>insulating material</b>	PPA-GF
<b>contact material</b>	Spring Steel, Copper
<b>core cross-section min.</b>	0.2 mm <sup>2</sup>
<b>core cross-section max.</b>	0.75 mm <sup>2</sup>
<b>impulse voltage rating</b>	4.0 kV
<b>flammability rating</b>	V-0
<b>max. Ambient Temperature Operation</b>	105 °C
<b>type of conductor solid</b>	yes
<b>type of conductor flexible</b>	yes
<b>type of conductor stranded</b>	yes
<b>stripping length</b>	8.0-9.0 mm
<b>pin spacing</b>	4.0 mm
<b>lower limit temperature</b>	-40 °C
<b>upper limit temperature</b>	150 °C
<b>Approbation EN60947</b>	SMDflat345_EN60947_20160524_VDE_40044300_web.pdf
<b>Approbation UL</b>	SMDflat 345_20150710_UL_E220480_1-02_web.pdf

## Accessories

---

<b>SMDflat 345 KU/ 2</b>	351152
<b>SMDflat WKZ</b>	351199

---