

Product: <u>8024</u> ⊠	
Bus Bar Wire, #28 Sol TC, QQ	-W-343G
😭 Request Sample	

Product Description

Bus Bar Wire, 28AWG (Solid) Tinned Copper, QQ-W-343G

Technical Specifications

Physical Characteristics (Overall)

AWG	Stranding	Material	No. of Conductors	
28	Solid	TC - Tinned Copper	1	
Cond	uctor Count:		1	
sula	tion			
Mat	terial			
No In:	sulation			
	tru oti o n	and Dimensions		
Jons	struction	and Dimensions		
Circul	ar Mil Area (0	CMA)1:	164	
Elect	rical Cha	racteristics		
	ctor DCR			
	nal Conduct	or DCR		
65.3 (Dhm/1000ft			
Nech	nanical Cl	haracteristics		
Bulk (Cable Weight	:	1 lbs/1000ft	
Stor	dards			
stall	ualus			
	VM Style:		N/A	
	VM Style: y Specificatio	on:	N/A N/A	
Milita	y Specificatio			
Milita Appl	y Specificatio		N/A	
Militar Appl EU Di	y Specification	vironmental and	N/A	
Militar Appl EU Di EU Di	y Specification icable En rective 2000/ rective 2003/	vironmental and	N/A I Other Programs Yes	
Militar Appl EU Di EU Di EU Di	y Specification icable En rective 2000/ rective 2003/ rective 2011/	vironmental and /53/EC (ELV): /96/EC (BFR):	N/A I Other Programs Yes Yes	
Militar Appl EU Di EU Di EU Di	y Specification icable En rective 2000/ rective 2003/ rective 2011/	/53/EC (ELV): /96/EC (BFR): /65/EU (ROHS II): /19/EU (WEEE):	N/A Conter Programs Yes Yes Yes Yes	
Militar Appl EU Di EU Di EU Di EU Di	y Specification icable En rective 2000/ rective 2003/ rective 2011/ rective 2012/	Vironmental and /53/EC (ELV): /96/EC (BFR): /65/EU (ROHS II): /19/EU (WEEE): /863/EU:	N/A Cother Programs Yes Yes Yes Yes Yes	EC (BFR)
Militar Appl EU Di EU Di EU Di EU Di EU Di	y Specification icable En rective 2000/ rective 2003/ rective 2011/ rective 2012/ rective 2015/	Vironmental and /53/EC (ELV): /96/EC (BFR): /65/EU (ROHS II): /19/EU (WEEE): /863/EU:	N/A Ves Ves Ves Ves Ves Ves Ves Ves	EC (BFR)
Militar EU Di EU Di EU Di EU Di EU Di EU Di EU Ci	y Specification icable En rective 2000/ rective 2003/ rective 2011/ rective 2012/ rective 2015/ rective Comp E Mark:	Vironmental and /53/EC (ELV): /96/EC (BFR): /65/EU (ROHS II): /19/EU (WEEE): /863/EU:	N/A Other Programs Yes Yes Yes Yes Yes EU Directive 2003/11/8 Yes	EC (BFR)

UL voltage rating: N/A

Plenum/Non-Plenum

Plenum (Y/N):	No	

Part Number

Variants

	ltem #	Color	Putup Type	Length	UPC
	8024 000100	None	Reel	100 ft	612825194408
	8024 0001000	None	Reel	1,000 ft	612825194415

History

Update and Revision: Revision Number: 0.256 Revision Date: 04-28-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.