



**Product:** [Ind REVConn Core](#) 

DataTuff Industrial REVConnect RJ45 Core

## Product Description

Universal Industrial REVConnect Core that Can Plug into Jack or Plug

## Technical Specifications

### Product Overview

Suitable Applications:	Up to TIA Category 6A, ISO Class EA, 10GBASE-T
------------------------	--

### Physical Characteristics (Overall)

Height:	0.58
Width:	0.46
Depth:	0.56
Wiring Scheme:	T568A/B
Packaging:	50 units packaged in a plastic bag.
Weight:	0.370 lbs

### Connectors

#### Materials

Description	Material	Type
Front Connection	10uin Gold plated contacts over Nickel	Ind REVConnect
Connector Body	PBT - UL94V-0	

### Electrical Characteristics

Dielectric Strength:	1,000V RMS @ 60 Hz for 1 minute (Signals to Ground)
Current Rating:	1.500 A
Insulation Resistance:	500 M-Ohm Minimum
Max Contact Resistance:	20 mOhm
Termination Resistance:	2.5 m-Ohm

### Temperature Range

Installation Temp Range:	-40°C To +70°C
Storage Temp Range:	-40°C To +70°C
Operating Temp Range:	-40°C To +70°C

### Mechanical Characteristics

Tool Compatibility:	RVUTT01 Termination Tool
Termination Rear Connection:	Mated Connection
Termination Rear Connection Durability:	200 cycles
Cable/Connector Retention:	25 lbs.
Connector/Hardware Retention:	20 lbs
Plug/Connector Retention:	11.250 lbs

## Standards

UL Rating:	UL94V-0
Telecommunications Standards:	Up to Category 6A - TIA 568.C.2, Category 6A - ISO/IEC 11801:2002 Ed.2
IEEE Specification:	Power Over Ethernet (PoE) IEEE 802.3at type 1 and 2 (up to 30W), IEEE802.3bt/D1.7 type 3 and 4 (up to 100W), CISCO UPOE (up to 60W), Power over HDBaseTTM (up to 100W)
Other Specification:	UL 1863, IEC 60603-7, FCC part 68-F

## Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2006-07-01
MII Order #39 (China RoHS):	EUP 50

## Flammability, LSOH, Toxicity Testing

UL Flammability:	UL2043 Air Handling Spaces
Safety Listing:	c(UL)us Listed

## Part Number

Related Parts:	Compatible with Industrial RevConnect Jacks, Plugs and Couplers
----------------	---

## Variants

Item #	Color
RVUI00UEW-B50	Electric White

## Product Notes

Notes:	Suitable with Solid and Stranded 23 to 24 AWG, UTP and Shielded cables. Insulation O.D. Range 0.035 to 0.055 in., Cable Jacket O.D. Max. 0.370 in. Please see Installation Guide PX106876 and PX106884.
--------	---

## History

Update and Revision:	Revision Number: 0.19 Revision Date: 02-25-2020
----------------------	---

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.