

BMP®41 Materials

www.BradyID.com/bmp41

Portable Printers

BMP®41 Voice & Data Comm Material:

Wrap Around Wire & Cable Markers

- **B-498 Repositionable Vinyl Cloth Material** - Printer automatically repeats your text to fill the label for maximum readability. Special adhesive stays put, but marker can be removed and reapplied if necessary. Temp Range -40°F to 175°F (-40°C to 70°C). UL Recognized.




Figure 29



Diagram	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Wire Gauge	Max. Wire Dia. Inch (mm)	Labels/Roll
B-498 Repositionable Vinyl Cloth Material									
Fig. 29	M-7-498	B-498	Vinyl	BK on WT	0.500 (12.7)	0.500 (12.7)	22 - 16 Gauge	0.110 (2.8)	240
Fig. 29	M-11-498	B-498	Vinyl	BK on WT	0.500 (12.7)	0.750 (19.1)	16 - 10 Gauge	0.160 (4.1)	220
Fig. 29	M-163-498	B-498	Vinyl	BK on WT	0.500 (12.7)	1.000 (25.4)	12 - 10 Gauge	0.210 (5.3)	180
Fig. 29	M-48-498	B-498	Vinyl	BK on WT	0.750 (19.1)	1.000 (25.4)	12 - 10 Gauge	0.210 (5.3)	180
Fig. 29	M-49-498	B-498	Vinyl	BK on WT	1.000 (25.4)	1.000 (25.4)	12 - 10 Gauge	0.210 (5.3)	160
Fig. 29	M-131-498	B-498	Vinyl	BK on WT	0.500 (12.7)	1.000 (25.4)	10 - 4 Gauge	0.270 (6.7)	180
Fig. 29	M-91-498	B-498	Vinyl	BK on WT	1.000 (25.4)	1.500 (38.1)	10 - 4 Gauge	0.270 (6.7)	120

BMP®41 Voice & Data Comm Material:

Patch Panel, Punch Block, Desi Strip and Faceplate Labels

Create a fully-formatted serialized punch block label to fit your equipment or label your ports, jacks and outlets with adhesive labels or slide-in strips.

- **B-412 Polypropylene Tags** - Non-Adhesive Slide-in Strips
- **B-422 Polyester Material** - Permanent adhesive, good for powder-coated/textured surfaces. Best on flat surfaces. Temp. Range: -40°F to 212°F (-40°C to 100°C). UL recognized.




Figure 29



Figure 33



Diagram	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels/Roll
B-412 Polypropylene Tags							
Fig. 33	MC-375-412	B-412	Polypropylene	BK on WT	0.375 (9.5)	20 ft (6.1 m)	1 roll (cont.)
Fig. 33	MC-475-412	B-412	Polypropylene	BK on WT	0.475 (12.1)	20 ft (6.1 m)	1 roll (cont.)
Fig. 33	MC-625-412	B-412	Polypropylene	BK on WT	0.625 (15.8)	20 ft (6.1 m)	1 roll (cont.)
B-422 Polyester Material							
Fig. 33	MC-375-422	B-422	Polyester	BK on WT	0.375 (9.5)	25 ft (7.6 m)	1 roll (cont.)
Fig. 33	MC-475-422	B-422	Polyester	BK on WT	0.475 (12.1)	25 ft (7.6 m)	1 roll (cont.)
Fig. 29	M-7-422	B-422	Polyester	BK on WT	0.500 (12.7)	0.500 (12.7)	280
Fig. 29	M-89-422	B-422	Polyester	BK on WT	0.500 (12.7)	1.500 (38.1)	180
Fig. 29	M-90-422	B-422	Polyester	BK on WT	0.750 (19.1)	1.500 (38.1)	180
Fig. 29	M-47-422	B-422	Polyester	BK on WT	1.000 (25.4)	0.500 (12.7)	480

BMP®41 Voice & Data Comm Material:

Terminal Block Markers

Specially-designed markers that offer a highly unique adhesive and vinyl cloth construction for excellent holding power, while still allowing for clean removal and application. Compatible with LabelMark™ Software or Brady's mobile app to auto-serialize labels, which helps save you time.

- **B-498 Repositionable Vinyl Cloth Material** - Printer automatically repeats your text to fill the label for maximum readability. Special adhesive stays put, but marker can be removed and reapplied if necessary. Temp Range -40°F to 175°F (-40°C to 70°C). UL Recognized.



Figure 33




Diagram	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels/Roll
B-498 - Repositionable Vinyl Cloth Labels							
Fig. 33	MC-240-498	B-498	Vinyl	BK on WT	0.240 (6.1)	16 ft (4.9 m)	1 roll (cont.)
Fig. 33	MC-318-498	B-498	Vinyl	BK on WT	0.318 (8.1)	16 ft (4.9 m)	1 roll (cont.)
Fig. 33	MC-375-498	B-498	Vinyl	BK on WT	0.375 (9.5)	16 ft (4.9 m)	1 roll (cont.)