

BMP®41 Voice & Data Comm Material:

Equipment, Component, Panel and Rating Plate Labels

Equipment and component labels are long-lasting, durable materials that make it easy to identify control, electrical materials and more. Ideal for marking backer boards, DIN rail, relays, PLCs, switches and solenoids. Create serial or rating plates with barcodes, graphics and more with a flexible high-tack adhesive for easy and long-lasting adhesion.

- **B-422 Polyester Material** - Permanent adhesive, good for powder-coated/textured surfaces. Best on flat surfaces. Temp. Range: -40°F to 212°F (-40°C to 100°C). UL recognized.
- **B-428 Metalized Polyester Material** - Permanent adhesive, silver finish. Temp. Range: -40°F to 176°F (-40°C to 80°C). UL recognized.
- **B-483 Polyester Material** - Permanent adhesive for powder-coated/textured surfaces. Best on flat surfaces Temp. Range: -40°F to 248°F (-40°C to 120°C). UL recognized.
- **B-499 Nylon Cloth Material** - Permanent adhesive. Pliable for rough or smooth surfaces. Temp. Range: -94°F to 194°F (-70°C to 90°C). UL recognized.
- **B-595 Indoor/Outdoor Vinyl Material** - Permanent adhesive, very pliable, good for rough surfaces and outdoor use, wide range of colors. Temp. Range: -40°F to 248°F (-40°C to 120°C). UL recognized.




Figure 29




Figure 33

Diagram	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels/Roll
B-422 – Polyester Material							
Fig. 33	MC-375-422	B-422	Polyester	BK on WT	0.375 (9.5)	25 ft (7.6 m)	1 roll (cont.)
Fig. 33	MC-475-422	B-422	Polyester	BK on WT	0.475 (12.1)	25 ft (7.6 m)	1 roll (cont.)
Fig. 29	M-7-422	B-422	Polyester	BK on WT	0.500 (12.7)	0.500 (12.7)	280
Fig. 29	M-89-422	B-422	Polyester	BK on WT	0.500 (12.7)	1.500 (38.1)	180
Fig. 33	MC-500-422	B-422	Polyester	BK on WT	0.500 (12.7)	25 ft (7.6 m)	1 roll (cont.)
Fig. 33	MC-625-42	B-422	Polyester	BK on WT	0.625 (15.8)	25 ft (7.6 m)	1 roll (cont.)
Fig. 29	M-90-422	B-422	Polyester	BK on WT	0.750 (19.1)	1.500 (38.1)	180
Fig. 29	M-47-422	B-422	Polyester	BK on WT	1.000 (25.4)	0.500 (12.7)	480
Fig. 29	M-49-422	B-422	Polyester	BK on WT	1.000 (25.4)	1.000 (25.4)	260
Fig. 33	MC1-1000-422	B-422	Polyester	BK on WT	1.000 (25.4)	25 ft (7.6 m)	1 roll (cont.)
B-428 – Metalized Polyester Material							
Fig. 29	M-92-428-BB	B-422	Polyester	Bk on SV	0.500 (12.7)	1.130 (28.7)	239
Fig. 29	M-47-428	B-422	Polyester	BK on SV	1.000 (25.4)	0.500 (12.7)	480
Fig. 29	M-60-428	B-422	Polyester	BK on SV	1.000 (25.4)	2.000 (50.8)	140
B-483 – Ultra Aggressive Adhesive Polyester							
Fig. 29	M-60-483	B-422	Polyester	BK on WT	1.000 (25.4)	2.000 (50.8)	140
B-499 – Nylon Cloth Material							
Fig. 33	MC-375-499	B-499	Nylon Cloth	BK on WT	0.375 (9.5)	16 ft (4.9 m)	1 roll (cont.)
Fig. 33	MC-500-499	B-499	Nylon Cloth	BK on WT	0.500 (12.7)	16 ft (4.9 m)	1 roll (cont.)
Fig. 33	M-11-499	B-499	Nylon Cloth	BK on WT	0.750 (19.1)	0.500 (12.7)	1 roll (cont.)
Fig. 33	MC-750-499	B-499	Nylon Cloth	BK on WT	0.750 (19.1)	16 ft (4.9 m)	1 roll (cont.)
Fig. 33	M-130-499	B-499	Nylon Cloth	BK on WT	0.825 (20.9)	0.375 (9.5)	1 roll (cont.)
Fig. 33	M-84-499	B-499	Nylon Cloth	BK on WT	0.900 (22.8)	0.500 (12.7)	1 roll (cont.)
Fig. 33	M-131-499	B-499	Nylon Cloth	BK on WT	1.000 (25.4)	0.500 (12.7)	1 roll (cont.)
Fig. 33	M-128-499	B-499	Nylon Cloth	BK on WT	1.000 (25.4)	1.900 (48.3)	1 roll (cont.)
B-595 – Indoor/Outdoor Vinyl Material							
Fig. 33	MC-500-595-OR-BK	B-595	Vinyl	BK on OR*	0.500 (12.7)	25 ft (7.6 m)	1 roll (cont.)
Fig. 33	MC-750-595-OR-BK	B-595	Vinyl	BK on OR*	0.750 (19.1)	25 ft (7.6 m)	1 roll (cont.)
Fig. 33	MC1-1000-595-OR-BK	B-595	Vinyl	BK on OR*	1.000 (25.4)	25 ft (7.6 m)	1 roll (cont.)

* For additional general purpose tapes, refer to the Indoor/Outdoor Grade Facility and Safety Labels.



BMP®41 Magnet Accessory Available

The BMP®41 printer offers a heavy-duty magnet accessory that allows you to go hands-free. Apply the magnet to the back of your printer and then stick it to a magnetized surface or wall.

