TLS2200[®] Labeling System

BradyID.com/tls2200



TLS2200® Label Printer

A rugged, portable, and easy-to-use labeling solution with crisp, thermaltransfer quality printing and a variety of durable materials. Create custom labels for the most demanding applications including product bar code ID, electrical and datacomm marking, laboratory ID. security ID, and more.

TLS PC Link™ Label Printer

A small footprint and lightweight, rugged design makes the TLS PC Link printer a nice fit for a variety of medium volume (approximately 500 labels per print run) applications. It connects to a PC for use with the included LabelMark™ software or other Windows based programs.

The same basic design as the TLS 2200® allows you to utilize the same consumables (including bulk rolls) in both the TLS 2200 and the TLS PC Link.



Online Video!

Visit BradvID.com/tls2200 for more information or to view an online printer demo video.

Your Complete Printing Solution:

TLS Label Rolls	page 311
TLS Print Ribbons	page 323

TLS2200® Printer & Accessories

Catalog #	Description
TLS2200	TLS2200 Thermal Label Printer*
TLS2200-AC	TLS2200 AC Power Supply
TLSHM-QUICKCH	TLS2200 Battery Quick Charger

*Includes hard case, battery pack, battery charger, test labels (PTL-19-423), R6210 ribbon, cleaning strip, communications cable, manual, Quick Start Guide and 1 year Limited Warranty.

TLS PC Link® Printer & Accessories

Catalog #	Description
TLSPC	TLS PC Link Thermal Labeling System*
TLSPC-AC	Replacement power supply/battery charger
TLSPC-BP	Rechargeable battery pack
TLSPC-CABLE	Communications cable
PCK-5	Cleaning Kit (5 cleaning cards)

*Includes LabelMark™ labeling software, rechargeable battery pack, power supply/battery charger, R6210 ribbon, sample labels (PTL-19-423), Quick Start Guide, manuals, communications cable, Windows® drivers and 1 year Limited Warranty.

TLS2200® / TLS PC Link Pritner Specifications Max Labels Per Day Average 750 labels/day Print Resolution Print Technology Thermal Transfer Print Speed 12 mm/sec (0.47 in/sec) Various sizes from 0.25" Tape Widths (inches) to 2.00' Various sizes from 6.4 to Tape Widths (mm) 50.8 mm Max Label Width 2.00" (50.8mm) Max Print Width 1.810" (46.0mm) Memory 21,000 characters / None PTL-, BPTL- Series **Materials Supported** 500+ Stock Parts Continuous vs Continuous and die cut Die Cut Labels labels Connectivity Sprial Options PC Connectivity Yes Software LabelMark® / CodeSoft™ Compatibility Software Data Transfer from PC to printer Wireless No Connectivity Stand Alone Printing Yes Single Color Printing Color Capability Keyboard ABC / None **Backlit Screen Text Sizes** 1 to 19 (4 to 72 point) Multi-Line Print Yes **Print Rotation** Yes Serialization Yes Barcode 128, IFT 25, Codabar 44 on keypad / LabelMark Supported Symbols Symbols Portability Yes / No Banner Portrait Banner Label Types or Landscape, Wire, Patch Application Panel, Terminal Block, Desi **Functions** Strip, Fixed Length Circuit Board Labeling, Data Communications Labeling, Facility, Safety & Maintenance Identification, General & Industrial **Applications** Labeling, Laboratory Identification, Panel Identification, Security Identification, Wire & Cable Marking Rechargeable Battery, AC Power Supply Power (optional) 2.75 lbs (1.25kg) / 2.5 lbs Weight (1.13kg) Warranty 1 year

Create Custom Labels In Seconds



Wire & Cable Labeling



Voice & Data Communications



Industrial Barcode Labels



Asset ID



Circuit Board Labels



General ID .and many more!

