



## Thermal Transfer Printable Labels - # THT-83-427-0.5

<b>MATERIAL:</b>	Self-Laminating Vinyl
<b>SIZE:</b>	2.000" W x 7.000" H (50.800 mm W x 177.800 mm H)
<b>QTY/UOM:</b>	500/Roll
<b>CATALOG #:</b>	THT-83-427-0.5
<b>PRODUCT #:</b>	30548

### OVERVIEW [SPECIFICATIONS](#)

#### Description for Thermal Transfer Printable Labels

Printable, self-laminating vinyl labels for thermal transfer printers. Please Note: This material is UL recognized with its respective ribbon. See the "Recommended Ribbon Series" for the appropriate ribbon to use.

#### Specification Of Thermal Transfer Printable Labels

**Application(s):** Panel Identification, Wire & Cable Marking

**Agency:** UL Recognized

**Approval(s)/Compliance:**

**Size:** 2.000" W x 7.000" H (50.800 mm W x 177.800 mm H)

**Printable Area:** 2.000" W x 1.500" H (50.800 mm W x 38.100 mm H)

**Web Width:** 2.200" (55.88 mm)

**Label Type/Style:** Self-Laminating Label

**Vertical Repeat:** 7.187" (182.55 mm)

**Color:** White/Translucent

**Finish:** Matte

**Qty Per Row:** 1

**Material Type:** Vinyl

**Material Description:** Self-Laminating Vinyl

**Brady Material #:** [B-427](#)

**General ID Catalog:** [pg. 132](#)

**Recommended Ribbon Series:** 4300

**Acceptable Ribbon Series:** 6200, 4500 (colors)

**Printer Compatibility:** BBP81, Brady 1244, Brady 1344, Brady 200MVP Plus, Brady 2461, Brady 300MVP Plus, Brady 300X-Plus II, Brady 3481, Brady 360X-Plus II, Brady 600X-Plus II, Brady 6441, IP300, IP600, Tagus T200, Tagus T300, Thermal Transfer Printers

**Style:** Roll-Form, Radius Corners

**Special Properties:** Excellent abrasion and smudge resistance, Excellent water & oil resistance, Self-Extinguishing, Self-Laminating

**RoHS Compatibility:** Compliant with RoHS Directive. NOTE: All statements concerning RoHS Directive compliance refer to 2005/618/EC MCV amendment to RoHS Directive 2002/95/EC. Product compliance is based upon information provided by suppliers of the raw materials used by Brady to manufacture these products, or by independent laboratory testing of these products. As such, Brady makes no independent representations or warranties, express or implied, and assumes no liability in connection with the use of this information.

**QTY/UOM:** 500/Roll