







## RoHS Compliant



# PCIe 3+1xRS232 1MBaud

PX-420/ PX-431

### "SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"

/...../.



#### Features

- 3+1 port RS232
- PCI Express x1, x4, x8 & x16 lane slots socket size
- 256 Byte Tx and 256 Byte Rx FIFOs
- Up to 921,600 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

#### Options



PX-420: PCle 3+1xRS232 1MBaud

PX-431: PCle 3xRS232 1MBaud



#### Description

PCI Express Card providing four RS232 serial ports. Up to 921,600 data transfer rates and the 256 byte deep transmit and 256 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your PC.

PCI Express is the latest standard in PC connectivity.

With Brainboxes' industry renowned Lifetime Warranty and Lifetime Support! PX-420 - PCle 4xRS232 1MBaud version; PX-431 - PCle 3xRS232 1MBaud version.

#### Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows Server 2008 32 bit & 64 bit Editions
- Windows Vista 32 bit and 64 bit editions
- Windows Server 2003 32 bit & 64 bit Editions
- Windows XP 32 bit & 64 bit editions


As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.



ORDER			
Description			
PCle	3+1xRS232 1MBaud		
PCle	3xRS232 1MBaud		

Code PX-420 PX-431

+44(0) 151 220 2500 | sales@brainboxes.com | www.brainboxes.com





# PCle 3+1xRS232 1MBaud

#### PX-420/ PX-431: Full Specification

Port	Ports	3+1 x RS232
Pin 1         DCD         RS232 Pinout (9 pin Male)           Pin 2         RXD         1         5	Connector	DB9 connector (9 Pin Male)
Pin 3 TXD Pin 4 DTR	FIFO size	256 RX FIFO + 256 TX FIFO
Pin 5 GND Pin 6 DSR	Operating Distance	EIA - RS232 Standard
Pin 7 RTS Pin 8 CTS	Cable	1 PORT RS232 on fly lead
Pin 9 RI 6 9		
Port Settings	Baud Rate	921,600
921,600	Data Bits	5,6,7 or 8
<b>&gt; &gt; &gt;</b>	Parity	Odd, Even, None, Mark or Space
baud	Stop Bits	1, 1.5 or 2
	Flow Control	RTS/CTS DSR/DTR XON/XOFF
	Tx/Rx Modes	Point to Point
Interface	OS Compatibility	Windows Server 2008 32 bit & 64 bit Editions Windows Vista 32 bit & 64 bit Editions
PCI >> express		Windows Server 2003 32 bit & 64 bit Editions
EXPRESS		Windows XP 32 bit & 64 bit Editions
		Microsoft Windows 2000
	BUS	PCI Express x1, x4, x8 & x16 lane slots :
Approvals	Other Approvals	WEEE ROHS METL EMC: CE
	Microsoft Approvals	Microsoft Certified Gold Partner
		Windows Server 2008 32 bit & 64 bit editions Windows Vista 32 bit & 64 bit editions
		Windows Server 2003 32 bit & 64 bit editions Windows XP 32 bit &
		64 bit editions
General	PCB Layers	4
	Power Consumption	410mA @ 3.3V, 400mA @ 3.3V
	Weight	0.079 Kg
	Size	110x20x120 mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	PCIe 3+1xRS232 1MBaud / PCIe 3xRS232 1MBaud
		1 PORT RS232 on fly lead
Product Support	Warranty	Lifetime (online registration required)
(ETI)	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
		staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
European Electronics Industry Awards WINNER	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume
Manufacturer of the Year * * Made in the UK	Customisable	users. More Info: sales@brainboxes.com
	1	, č

Datasheet Version: 3.79 Published on: 2009/8/25