











RoHS Compliant



UC-268/UC-265

uPCI 4xRS232

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Description

Universal PCI card provides 4 industry standard RS232 serial COM ports in a single PCI slot, supplied with 9 pin cable.

Universal PCI is fully compatible with both 3.3Volt and 5Volt PCI slots.

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

Features

- 4 port RS232
- PCI 3.0
- 64 Byte Tx and 64 Byte Rx FIFOs
- Up to 115,200 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



UC-268. uPCI 4xRS232

UC-265 uPCI 4xRS232 DB25



Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows Server 2008 32 bit & 64 bit Editions
- Windows Vista 32 bit and 64 bit editions
- Windows Server 2003 32 bit & 64 bit Editions
- Windows XP 32 bit & 64 bit editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.















ORDER Description uPCI 4xRS232 uPCI 4xRS232 DB25

Code UC-268 UC-265

+44(0) 151 220 2500 | sales@brainboxes.com



uPCI 4xRS232

UC-268/UC-265: Full Specification

UC-208/UC-205. Full Specification		
Port	Ports	4 x RS232
Pin 1 DCD RS232 Pinout (9 pin Male)	Connector	DB9 connector (9 Pin Male)
Pin 2 RXD 1 5 Pin 3 TXD 1 5	FIFO size	64 RX FIFO + 64 TX FIFO
Pin 4 DTR Pin 5 GND	Operating Distance	EIA - RS232 Standard
Pin 6 DSR Pin 7 RTS Pin 8 CTS Pin 9 RI 6 9	Cable	37 WAY D TO: 4 x DB9 (9 Pin Male)
Port Settings	Baud Rate	115,200
115,200	Data Bits	5,6,7 or 8
> > > >	Parity	Odd, Even, None, Mark or Space
baud	Stop Bits	1, 1.5 or 2
	Flow Control	RTS/CTS DSR/DTR XON/XOFF
	Tx/Rx Modes	Point to Point
Interface	OS Compatibility	Windows Server 2008 32 bit & 64 bit Editions
		Windows Vista 32 bit & 64 bit Editions
PCI		Windows Server 2003 32 bit & 64 bit Editions Windows XP 32 bit & 64 bit Editions
		Microsoft Windows ME
	BUS	PCI 3.0 : Peripheral Component Interface
Approvals	Other Approvals	WEEE RoHS FCC Compliant EMC: CE
FC FC	Microsoft Approvals	Microsoft Certified Gold Partner
General	PCB Layers	4
	Power Consumption	210mA @ 5V, 60mA @ 12V
	Weight	0.073 Kg
	Size	125x20x120 mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	uPCI 4xRS232 / uPCI 4xRS232 DB25
		37 WAY D TO: 4 x DB9 (9 Pin Male)
Product Support	Warranty	Lifetime (online registration required)
, reduced employee	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
		staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
Elektra O5	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
WINNER Manufacturer of the Year Made in the UK	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com

Datasheet Version: 3.57 Published on: 2009/7/14