












## RoHS Compliant



### UC-302

### uPCI 2xRS232 1MBaud

### "SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



#### Features

- 2 port RS232
- PCI 3.0
- 128 Byte Tx and 128 Byte Rx FIFOs
- Up to 921,600 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

#### **Options**



UC-302: uPCI 2xRS232 1MBaud

#### Description

Universal PCI providing two RS232 serial ports. Up to 921,600 data transfer rates and the 128 byte deep transmit and 128 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your PC.

Universal PCI is fully compatible with both 3.3Volt and 5Volt PCI slots.

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

#### Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows Server 2008 & Windows 2000
- Windows Vista 32 bit and 64 bit editions
- Windows Server 2003 32 bit & 64 bit Editions
- Windows XP 32 bit & 64 bit editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.





















ORDER
Description
uPCI 2xRS232 1MBaud

Code UC-302

For alternative baud rates see UC-257 & UC-607



# uPCI 2xRS232 1MBaud

UC-302: Full Specification

oc-302. Tuli Specification		
Port	Ports	2 x RS232
Pin 1 DCD RS232 Pinout (9 pin Male)	Connector	DB9 connector (9 Pin Male)
Pin 2 RXD 1 5 Pin 3 TXD 1 5	FIFO size	128 RX FIFO + 128 TX FIFO
Pin 4 DTR Pin 5 GND	Operating Distance	EIA - RS232 Standard
Pin 6 DSR Pin 7 RTS	Cable	No Cable; Integrated Connector
Pin 9 RI 6 9		
Port Settings	Baud Rate	921,600
921,600	Data Bits	5,6,7 or 8
<b>&gt;</b> > >	Parity	Odd, Even, None, Mark or Space
baud	Stop Bits	1, 1.5 or 2
	Flow Control	RTS/CTS DSR/DTR XON/XOFF
	Tx/Rx Modes	Point to Point
Interface	OS Compatibility	Windows Server 2008 32 bit & 64 bit Editions
Interface	35 Compatibility	Windows Vista 32 bit & 64 bit Editions
PCI <sup>®</sup>		Windows Server 2003 32 bit & 64 bit Editions
		Windows XP 32 bit & 64 bit Editions Microsoft Windows 2000
	BUS	
Λ Ι	Other Approvals	PCI 3.0 : Peripheral Component Interface  WEEE ROHS EMC: CE
Approvals		
	Microsoft Approvals	Microsoft Certified Gold Partner Windows Server 2008 32 bit & 64 bit editions Windows Vista 32 bit &
ROHS CE		64 bit editions
SSEALED /		Windows Server 2003 32 bit & 64 bit editions Windows XP 32 bit &
		64 bit editions
General	PCB Layers	4
	Power Consumption	210mA @ 5V, 20mA @ 12V
	Weight	0.081 Kg
	Size	0x0x0 mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	uPCI 2xRS232 1MBaud /
		No Cable; Integrated Connector
Product Support	Warranty	Lifetime (online registration required)
GETTIN GETTIN	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
		staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
Elektra O5	Made In	Manufactured in the UK by Brainboxes Winner 2005 European
European Electronics Industry Awards		Electronics Industry Awards "Manufacturer of the Year"
WINNER Manufacturer of the Year Made in the UK	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com

Datasheet Version: 3.57 Published on: 2009/7/14