CU-3286 TD CU-3286-MB CUR-3286 TD CUR-3286-MB CUR-3286-C TD CUR-3286-CMB PART PART UTILIBOX (STYLE A) NAME No. MATERIAL: BODY AND STANDARD COVERS SIX (6) #4-40 x 0.500" LG, SCREWS ABS THERMOPLASTIC (FLAMMABILITY RATING UL94-5VA) SUPPLIED FOR ASSEMBLING COVER RECESSED COVERS (CUR-) TO BODY ABS THERMOPLASTIC (FLAMMABILITY RATING UL94-5VA) CLEAR COVERS (-C) MOUNTING BOSSES USE EITHER M2.5 ABS THERMOPLASTIC (FLAMMABILITY RATING UL94V-2) METRIC OR #4 STD. SHEET METAL SCREWS x 0.250" LG. FINISH (NOT SUPPLIED) BODY AND STANDARD COVERS ARE BLACK TEXTURED RECESSED (CUR-) AND CLEAR COVERS (-C) ARE SMOOTH FINISH - 10,151 -**-**─ 0.125 4.585 -- 4.583 0.125 -4.656 TEXTURED FLUSH OR 5.170 ∭ 6.151 0.030 RECESSED SMOOTH 8.656 **((3)** #4-40 THREADED INSERT - 11.400 -(6) PLACES 4.585 -**-** 4.585 -3.0000 **⊚** ` 0 -0.250 DIA. B□SS (8) PLACES

-4.500-

— 0.750 - 3.875 - 6.000

0.125

0.250 DIA. (4) HOLES (TO FIT A #10 SCREW)

4.000

└0.086 x 0.250 DEEP

3.875 -

0.250 (TYP)

- U.1U5

10.750

- 10.000

(8) PLACES

5.170 (3 PLACES)

6.151