

1062.2

SL 2,5/35/ZRL GNYE

SL 2,5/35/ZRL GNYE



Protective earth terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 6 mm, Colour: Green-yellow

Business data

Product description	Protective earth terminal
Packaging unit	100
Quantity unit	PC
Weight per piece (not including packaging)	24.2
Weight per piece (including packaging)	25
Unit of weight	G
Customs number	85369010
Country of origin	DE

1062.2

SL 2,5/35/ZRL GNYE

SL 2,5/35/ZRL GNYE

Technical Data

Dimensions

Length	62 mm
Width	6 mm
Height TS 35/7.5	47 mm

Ratings

Rated cross-section	2.5 mm ²
Overvoltage category	III
Contamination degree	3

1062.2

SL 2,5/35/ZRL GNYE

SL 2,5/35/ZRL GNYE

Technical Data

Connection data

Connection principle	Screw connection
Connection position	Lateral
Connections	4
Number of terminals per level	2
Number of levels	1
Wire cross-section single-core (rigid) / stranded, min.	0.2 mm ²
Wire cross-section single core (rigid)/stranded, max.	2.5 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	2.5 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm ²
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm ²
Wire cross-section AWG, min.	22
Wire cross-section AWG, max.	12
Stripping length	9 mm
Screw head	Slotted
Screw threading	M 2,5
Tightening torque, min.	0.4 Nm
Tightening torque, max.	0.8 Nm

1062.2

SL 2,5/35/ZRL GNYE

SL 2,5/35/ZRL GNYE

Technical Data

Materials

Insulation housing	Polyamide 6.6
--------------------	---------------

Flammability class UL 94	V-2
--------------------------	-----

Working temperature, min.	-40 °C
---------------------------	--------

Working temperature, max.	105 °C
---------------------------	--------

Further technical data

Mounting type	Mounting rail TS 35/7,5
---------------	-------------------------

Gauge plug acc. to EN 60 947-1	A3
--------------------------------	----

1062.2

SL 2,5/35/ZRL GNYE

SL 2,5/35/ZRL GNYE

Approvals

Standards and regulations

EAC approval	TR ZU 004/2011
--------------	----------------


EAC approval granted	✓
----------------------	---

1062.2

SL 2,5/35/ZRL GNYE

SL 2,5/35/ZRL GNYE

Media



M2.5 

EAC

1062.2

SL 2,5/35/ZRL GNYE

SL 2,5/35/ZRL GNYE

Accessories

End plate




End plate, Width: 1.5 mm, Colour: Beige

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2575.2	AP 2,5/RL	4044211053680	50 PC

Quick-marking



Terminal marker / Pocket Maxicard, Length: 5 mm,
Width: 6 mm, Colour: White

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
4702.7	PMC SB 6/50 WH	4044211089986	500 PC

1062.2

SL 2,5/35/ZRL GNYE

SL 2,5/35/ZRL GNYE

Accessories

Screw driver



Screwdriver with bare blade, Colour: Black-grey

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1085.0	SDB 0,5x3,0	4044211014643	1 PC
