

1198.2

SL 35/32 GNYE

SL 35/32 GNYE



Protective earth terminal, Screw connection, Mounting type: Mounting rail TS 32, Rated cross-section: 35 mm², Width: 16 mm, Colour: Green-yellow

Business data

Product description	Protective earth terminal
Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	94
Weight per piece (including packaging)	97.2
Unit of weight	G
Customs number	85369010
Country of origin	DE

1198.2

SL 35/32 GNYE

SL 35/32 GNYE

Technical Data

Dimensions

Length	58 mm
--------	-------

Width	16 mm
-------	-------

Height TS 32	76 mm
--------------	-------

Ratings

Rated cross-section	35 mm ²
---------------------	--------------------

Overvoltage category	III
----------------------	-----

Contamination degree	3
----------------------	---

1198.2

SL 35/32 GNYE

SL 35/32 GNYE

Technical Data

Connection data

Connection principle	Screw connection
Connection position	Lateral
Connections	2
Number of terminals per level	2
Number of levels	1
Wire cross-section single-core (rigid) / stranded, min.	2.5 mm ²
Wire cross-section single core (rigid)/stranded, max.	50 mm ²
Wire cross-section stranded, min.	2.5 mm ²
Wire cross-section stranded, max.	35 mm ²
Wire cross-section stranded with wire-end ferrules, min.	2.5 mm ²
Wire cross-section stranded with wire-end ferrules, max.	35 mm ²
Wire cross-section AWG, min.	12
Wire cross-section AWG, max.	2
Stripping length	20 mm
Screw head	Slotted
Screw threading	M 6
Tightening torque, min.	2.5 Nm
Tightening torque, max.	5 Nm

1198.2

SL 35/32 GNYE

SL 35/32 GNYE

Technical Data

Materials

Insulation housing	Polyamide 6.6
--------------------	---------------

Flammability class UL 94	V-2
--------------------------	-----

Working temperature, min.	-40 °C
---------------------------	--------

Working temperature, max.	105 °C
---------------------------	--------

Further technical data

Mounting type	Mounting rail TS 32
---------------	---------------------

Gauge plug acc. to EN 60 947-1	B9
--------------------------------	----

Number of cross-connection channels	1
-------------------------------------	---

1198.2

SL 35/32 GNYE

SL 35/32 GNYE

Approvals

Standards and regulations

EAC approval	TR ZU 004/2011
--------------	----------------

EAC approval granted	✓
----------------------	---

CSA approval

CSA approval	C22.2 No 158
--------------	--------------

CSA approval granted	✓
----------------------	---

CSA wire cross-section AWG, min.	12
----------------------------------	----

CSA wire cross-section AWG, max.	2
----------------------------------	---

CSA stripping length	20 mm
----------------------	-------

CSAus approval

CSAus approval	UL 1059
----------------	---------

CSAus approval granted	✓
------------------------	---

CSAus wire cross-section AWG, min.	12
------------------------------------	----

CSAus wire cross-section AWG, max.	2
------------------------------------	---

CSAus stripping length	20 mm
------------------------	-------

1198.2

SL 35/32 GNYE

SL 35/32 GNYE

Media



M6



ERC


1198.2

SL 35/32 GNYE

SL 35/32 GNYE

Accessories

Quick-marking



Terminal marker / Pocket Maxicard, Length: 5 mm,
Width: 6 mm, Colour: White

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
4702.7	PMC SB 6/50 WH	4044211089986	500 PC

Screw driver



Screwdriver with bare blade, Colour: Black-grey

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1088.0	SDB 1,2x6,5	4044211014810	1 PC
