


1323.2

BKA 2,5/4 BG

BKA 2,5/4 BG



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 2.5 mm², Colour: Beige

Business data

| | |
|--|--|
| Product description | Feed-through terminal for direct mount |
| Packaging unit | 50 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 19.8 |
| Weight per piece (including packaging) | 20.74 |
| Unit of weight | G |
| Customs number | 85369010 |
| Country of origin | DE |

1323.2

BKA 2,5/4 BG

BKA 2,5/4 BG

Technical Data

Dimensions

| | |
|---------------------------------------|---------|
| Length | 34.6 mm |
| Height | 23 mm |
| Hole spacing (mid-point to mid-point) | 27.5 mm |
| Pitch | 5 mm |

Ratings

| | |
|-----------------------|---------------------|
| Rated voltage | 400 V |
| Rated current | 24 A |
| Rated cross-section | 2.5 mm ² |
| Rated impulse voltage | 6 kV |
| Overvoltage category | III |
| Contamination degree | 3 |

1323.2

BKA 2,5/4 BG

BKA 2,5/4 BG

Technical Data

Connection data

| | |
|--|---------------------|
| Connection principle | Screw connection |
| Connection position | Lateral |
| Connections | 8 |
| Number of terminals per level | 2 |
| Number of levels | 1 |
| Wire cross-section single-core (rigid) / stranded, min. | 0.2 mm ² |
| Wire cross-section single core (rigid)/stranded, max. | 4 mm ² |
| Wire cross-section stranded, min. | 0.2 mm ² |
| Wire cross-section stranded, max. | 4 mm ² |
| Wire cross-section stranded with wire-end ferrules, min. | 0.2 mm ² |
| Wire cross-section stranded with wire-end ferrules, max. | 2.5 mm ² |
| Wire cross-section AWG, min. | 22 |
| Wire cross-section AWG, max. | 12 |
| Stripping length | 7 mm |
| Screw head | Slotted |
| Screw threading | M 2,5 |
| Tightening torque, min. | 0.4 Nm |
| Tightening torque, max. | 0.8 Nm |

1323.2

BKA 2,5/4 BG

BKA 2,5/4 BG

Technical Data

Materials

| | |
|---------------------------|---------------|
| Insulation housing | Polyamide 6.6 |
| Flammability class UL 94 | V-2 |
| Working temperature, min. | -40 °C |
| Working temperature, max. | 105 °C |

Further technical data

| | |
|--------------------------------|---------------|
| Mounting type | Mounting face |
| Gauge plug acc. to EN 60 947-1 | A3 |
| End plate required | ✓ |

1323.2

BKA 2,5/4 BG

BKA 2,5/4 BG

Approvals

Standards and regulations

| | |
|--------------|----------------|
| EAC approval | TR ZU 004/2011 |
|--------------|----------------|

| | |
|----------------------|---|
| EAC approval granted | ✓ |
|----------------------|---|

cUL Recognized

| | |
|----------------|--------------|
| cUL Recognized | C22.2 No 158 |
|----------------|--------------|

| | |
|----------------|---|
| cUL Recognized | ✓ |
|----------------|---|

| | |
|-------------------------------|-------|
| cUL Usegroup B: rated voltage | 300 V |
|-------------------------------|-------|

| | |
|-------------------------------|------|
| cUL Usegroup B: rated current | 20 A |
|-------------------------------|------|

| | |
|-------------------------------|-------|
| cUL Usegroup C: rated voltage | 300 V |
|-------------------------------|-------|

| | |
|-------------------------------|------|
| cUL Usegroup C: rated current | 20 A |
|-------------------------------|------|

| | |
|--|----|
| cUL wire cross-section single-core (rigid) AWG, min. | 22 |
|--|----|

| | |
|--|----|
| cUL wire cross-section single-core (rigid) AWG, max. | 12 |
|--|----|

| | |
|---|----|
| cUL wire cross-section stranded AWG, min. | 22 |
|---|----|

| | |
|---|----|
| cUL wire cross-section stranded AWG, max. | 12 |
|---|----|

| | |
|------------|--------|
| cUL torque | 5.3 Nm |
|------------|--------|

| | |
|-------------------|----|
| cUL wire material | Cu |
|-------------------|----|

1323.2

BKA 2,5/4 BG

BKA 2,5/4 BG

Approvals

KEMA KEUR approval

| | |
|---|---------------------|
| KEMA KEUR approval | EN 60947-7-1 |
| KEMA KEUR approval granted | ✓ |
| KEMA rated voltage | 400 V |
| KEMA rated current | 24 A |
| KEMA rated impulse voltage | 6 kV |
| KEMA wire cross-section single core (rigid), min. | 0.2 mm ² |
| KEMA wire cross-section single-core (rigid), max. | 4 mm ² |
| KEMA wire cross-section stranded, min. | 0.2 mm ² |
| KEMA wire cross-section stranded, max. | 4 mm ² |
| KEMA torque, min. | 0.4 Nm |
| KEMA torque, max. | 0.8 Nm |

1323.2

BKA 2,5/4 BG

BKA 2,5/4 BG

Approvals

UL Recognized


| | |
|---|-----------|
| UL Recognized | UL 1059 |
| UL Recognized granted | ✓ |
| UL Usegroup B: rated voltage | 300 V |
| UL Usegroup B: rated current | 20 A |
| UL Usegroup C: rated voltage | 300 V |
| UL Usegroup C: rated current | 20 A |
| UL wire cross-section single-core (rigid) AWG, min. | 22 |
| UL wire cross-section single-core (rigid) AWG, max. | 12 |
| UL wire cross-section stranded AWG, min. | 22 |
| UL wire cross-section stranded AWG, max. | 12 |
| UL torque | 5.3 Lb In |
| UL wire material | Cu |
| UL factory wiring | ✓ |
| UL field wiring | ✓ |

1323.2

BKA 2,5/4 BG

BKA 2,5/4 BG

Media



M2.5



EAC



CE  **US**

1323.2

BKA 2,5/4 BG

BKA 2,5/4 BG

Accessories

External insulated cross-connector



External insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 50.1 mm, Rated current: 27 A; Colour: Yellow

In general

| Order number | Article designation | GTIN (EAN) | Packaging unit |
|--------------|---------------------|---------------|----------------|
| 2045.0 | AQI 10/5/11 | 4044211048501 | 10 PC |



External insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 9.26 mm, Rated current: 27 A; Colour: Yellow

In general

| Order number | Article designation | GTIN (EAN) | Packaging unit |
|--------------|---------------------|---------------|----------------|
| 2032.0 | AQI 2/5/11 | 4044211048341 | 50 PC |


1323.2

BKA 2,5/4 BG

BKA 2,5/4 BG

Accessories


External insulated cross-connector



External insulated cross-connector, No. of poles: 3,
Mounting type: Plug in, Width: 14.36 mm, Rated
current: 27 A; Colour: Yellow

In general

| Order number | Article designation | GTIN (EAN) | Packaging unit |
|--------------|---------------------|---------------|----------------|
| 2033.0 | AQI 3/5/11 | 4044211048358 | 50 PC |



External insulated cross-connector, No. of poles: 4,
Mounting type: Plug in, Width: 19.46 mm, Rated
current: 27 A; Colour: Yellow

In general

| Order number | Article designation | GTIN (EAN) | Packaging unit |
|--------------|---------------------|---------------|----------------|
| 2044.0 | AQI 4/5/11 | 4044211048495 | 50 PC |


1323.2

BKA 2,5/4 BG

BKA 2,5/4 BG

Accessories

Quick-marking



Terminal marker / Pocket Maxicard, Length: 5 mm,
Width: 5 mm, Colour: White

In general

| Order number | Article designation | GTIN (EAN) | Packaging unit |
|--------------|---------------------|---------------|----------------|
| 4600.7 | PMC SB 5/50 WH | 4044211088903 | 500 PC |

Screw driver



Screwdriver with bare blade, Colour: Black-grey

In general

| Order number | Article designation | GTIN (EAN) | Packaging unit |
|--------------|---------------------|---------------|----------------|
| 1085.0 | SDB 0,5x3,0 | 4044211014643 | 1 PC |
