

1391.5

TRK 1,5/STB BU

TRK 1,5/STB BU



Disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Width: 6 mm, Colour: Blue

Business data

| | |
|--|---------------------|
| Product description | Disconnect terminal |
| Packaging unit | 100 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 10.2 |
| Weight per piece (including packaging) | 10.73 |
| Unit of weight | G |
| Customs number | 85369010 |
| Country of origin | DE |

1391.5

TRK 1,5/STB BU

TRK 1,5/STB BU

Technical Data

Dimensions

| | |
|------------------|---------|
| Length | 48 mm |
| Width | 6 mm |
| Height TS 35/7.5 | 48.3 mm |
| Height TS 32 | 52.8 mm |

Ratings

| | |
|-----------------------|---------------------|
| Rated voltage | 400 V |
| Rated current | 10 A |
| Rated cross-section | 2.5 mm ² |
| Rated impulse voltage | 4 kV |
| Overvoltage category | III |
| Contamination degree | 3 |

1391.5

TRK 1,5/STB BU

TRK 1,5/STB BU

Technical Data

Connection data

| | |
|--|---------------------|
| Connection principle | Screw connection |
| Connection position | Lateral |
| Connections | 2 |
| Number of terminals per level | 2 |
| Number of levels | 1 |
| Wire cross-section single-core (rigid) / stranded, min. | 0.2 mm ² |
| Wire cross-section single core (rigid)/stranded, max. | 4 mm ² |
| Wire cross-section stranded, min. | 0.2 mm ² |
| Wire cross-section stranded, max. | 4 mm ² |
| Wire cross-section stranded with wire-end ferrules, min. | 0.2 mm ² |
| Wire cross-section stranded with wire-end ferrules, max. | 2.5 mm ² |
| Wire cross-section AWG, min. | 22 |
| Wire cross-section AWG, max. | 12 |
| Stripping length | 8 mm |
| Screw head | Slotted |
| Screw threading | M 3 |
| Tightening torque, min. | 0.5 Nm |
| Tightening torque, max. | 1 Nm |

1391.5

TRK 1,5/STB BU

TRK 1,5/STB BU

Technical Data

Materials

| | |
|--------------------|---------------|
| Insulation housing | Polyamide 6.6 |
|--------------------|---------------|

| | |
|--------------------------|-----|
| Flammability class UL 94 | V-2 |
|--------------------------|-----|

| | |
|---------------------------|--------|
| Working temperature, min. | -40 °C |
|---------------------------|--------|

| | |
|---------------------------|--------|
| Working temperature, max. | 105 °C |
|---------------------------|--------|

Further technical data

| | |
|---------------|-----------------------------------|
| Mounting type | Mounting rail TS 35/7.5 and TS 32 |
|---------------|-----------------------------------|

| | |
|--------------------------------|----|
| Gauge plug acc. to EN 60 947-1 | A4 |
|--------------------------------|----|

| | |
|--------------------|---|
| End plate required | ✓ |
|--------------------|---|

| | |
|---------------------------------|---|
| Number of test pick-off options | 2 |
|---------------------------------|---|

| | |
|--------------------------------|---|
| Built-in test socket available | ✓ |
|--------------------------------|---|

| | |
|---------------------------------|------------|
| Version of lengthwise partition | Swivelling |
|---------------------------------|------------|

1391.5

TRK 1,5/STB BU

TRK 1,5/STB BU

Approvals

cUL Recognized

| | |
|--|--------------|
| cUL Recognized | C22.2 No 158 |
| cUL Recognized | ✓ |
| cUL Usegroup B: rated voltage | 600 V |
| cUL Usegroup B: rated current | 15 A |
| cUL Usegroup C: rated voltage | 600 V |
| cUL Usegroup C: rated current | 15 A |
| cUL wire cross-section single-core (rigid) AWG, min. | 22 |
| cUL wire cross-section single-core (rigid) AWG, max. | 12 |
| cUL wire cross-section stranded AWG, min. | 22 |
| cUL wire cross-section stranded AWG, max. | 12 |
| cUL torque | 7 Nm |
| cUL wire material | Cu |

1391.5

TRK 1,5/STB BU

TRK 1,5/STB BU

Approvals

UL Recognized


| | |
|---|---------|
| UL Recognized | UL 1059 |
| UL Recognized granted | ✓ |
| UL Usegroup B: rated voltage | 600 V |
| UL Usegroup B: rated current | 15 A |
| UL Usegroup C: rated voltage | 600 V |
| UL Usegroup C: rated current | 15 A |
| UL wire cross-section single-core (rigid) AWG, min. | 22 |
| UL wire cross-section single-core (rigid) AWG, max. | 12 |
| UL wire cross-section stranded AWG, min. | 22 |
| UL wire cross-section stranded AWG, max. | 12 |
| UL torque | 7 Lb In |
| UL wire material | Cu |
| UL factory wiring | ✓ |
| UL field wiring | ✓ |

1391.5

TRK 1,5/STB BU

TRK 1,5/STB BU

Media



M3



CRAUS[®]

1391.5

TRK 1,5/STB BU

TRK 1,5/STB BU

Accessories

External insulated cross-connector



External insulated cross-connector, No. of poles: 2,
Mounting type: Plug in, Width: 10.8 mm, Rated
current: 27 A; Colour: Yellow

In general

| Order number | Article designation | GTIN (EAN) | Packaging unit |
|--------------|---------------------|---------------|----------------|
| 2064.0 | AQI 2/6/17 | 4044211048709 | 50 PC |



External insulated cross-connector, No. of poles: 3,
Mounting type: Plug in, Width: 16.9 mm, Rated
current: 27 A; Colour: Yellow

In general

| Order number | Article designation | GTIN (EAN) | Packaging unit |
|--------------|---------------------|---------------|----------------|
| 2065.0 | AQI 3/6/17 | 4044211048716 | 50 PC |


1391.5

TRK 1,5/STB BU

TRK 1,5/STB BU

Accessories

External insulated cross-connector



External insulated cross-connector, No. of poles: 4, Mounting type: Plug in, Width: 23 mm, Rated current: 27 A; Colour: Yellow

In general

| Order number | Article designation | GTIN (EAN) | Packaging unit |
|--------------|---------------------|---------------|----------------|
| 2066.0 | AQI 4/6/17 | 4044211048723 | 50 PC |

End bracket



End stop, Mounting type: Mounting rail TS 35/7.5, Width: 9.5 mm, Colour: Beige

In general

| Order number | Article designation | GTIN (EAN) | Packaging unit |
|--------------|---------------------|---------------|----------------|
| 2828.0 | ES 35/K/ST | 4044211055547 | 50 PC |

1391.5

TRK 1,5/STB BU

TRK 1,5/STB BU

Accessories

Test plug




Test plug, Colour: Red

In general

| Order number | Article designation | GTIN (EAN) | Packaging unit |
|--------------|---------------------|---------------|----------------|
| 2007.0 | PS 2,3 | 4044211048105 | 20 PC |

Quick-marking



Terminal marker / Pocket Maxicard, Length: 5 mm,
Width: 8 mm, Colour: White

In general

| Order number | Article designation | GTIN (EAN) | Packaging unit |
|--------------|---------------------|---------------|----------------|
| 9323.7 | PMC SB 8/40 WH | 4044211129231 | 400 PC |

1391.5

TRK 1,5/STB BU

TRK 1,5/STB BU

Accessories

Screw driver



Screwdriver with bare blade, Colour: Black-grey

In general

| Order number | Article designation | GTIN (EAN) | Packaging unit |
|--------------|---------------------|---------------|----------------|
| 1086.0 | SDB 0,6x3,5 | 4044211014797 | 1 PC |
