

1393.5

TRK 1,5/15/STB BU

TRK 1,5/15/STB BU



Disconnect terminal, Screw connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 2.5 mm<sup>2</sup>, Width: 6 mm, Colour: Blue

## Business data

Product description	Disconnect terminal
Packaging unit	100
Quantity unit	PC
Weight per piece (not including packaging)	9.2
Weight per piece (including packaging)	9.93
Unit of weight	G
Customs number	85369010
Country of origin	DE

**1393.5**

**TRK 1,5/15/STB BU**

**TRK 1,5/15/STB BU**

## Technical Data

---

### Dimensions

---

Length	48 mm
Width	6 mm
Height TS 15/5.5	38.3 mm

### Ratings

---

Rated voltage	400 V
Rated current	10 A
Rated cross-section	2.5 mm <sup>2</sup>
Rated impulse voltage	4 kV
Overvoltage category	III
Contamination degree	3

**1393.5**

**TRK 1,5/15/STB BU**

**TRK 1,5/15/STB BU**

## Technical Data

---

### Connection data

Connection principle	Screw connection
Connection position	Lateral
Connections	2
Number of terminals per level	2
Number of levels	1
Wire cross-section single-core (rigid) / stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section single core (rigid)/stranded, max.	4 mm <sup>2</sup>
Wire cross-section stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded, max.	4 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm <sup>2</sup>
Wire cross-section AWG, min.	22
Wire cross-section AWG, max.	12
Stripping length	8 mm
Screw head	Slotted
Screw threading	M 3
Tightening torque, min.	0.5 Nm
Tightening torque, max.	1 Nm

**1393.5**

**TRK 1,5/15/STB BU**

**TRK 1,5/15/STB BU**

## Technical Data

---

### Materials

---

Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

### Further technical data

---

Mounting type	TS 15
Gauge plug acc. to EN 60 947-1	A4
End plate required	✓
Number of test pick-off options	2
Built-in test socket available	✓
Version of lengthwise partition	Swivelling

**1393.5**

**TRK 1,5/15/STB BU**

**TRK 1,5/15/STB BU**

## Approvals

---

### cUL Recognized

cUL Recognized	C22.2 No 158
cUL Recognized	✓
cUL Usegroup B: rated voltage	600 V
cUL Usegroup B: rated current	15 A
cUL Usegroup C: rated voltage	600 V
cUL Usegroup C: rated current	15 A
cUL wire cross-section single-core (rigid) AWG, min.	22
cUL wire cross-section single-core (rigid) AWG, max.	12
cUL wire cross-section stranded AWG, min.	22
cUL wire cross-section stranded AWG, max.	12
cUL torque	7 Nm
cUL wire material	Cu

1393.5

TRK 1,5/15/STB BU

TRK 1,5/15/STB BU

## Approvals

---

### UL Recognized

UL Recognized	UL 1059
UL Recognized granted	✓
UL Usegroup B: rated voltage	600 V
UL Usegroup B: rated current	15 A
UL Usegroup C: rated voltage	600 V
UL Usegroup C: rated current	15 A
UL wire cross-section single-core (rigid) AWG, min.	22
UL wire cross-section single-core (rigid) AWG, max.	12
UL wire cross-section stranded AWG, min.	22
UL wire cross-section stranded AWG, max.	12
UL torque	7 Lb In
UL wire material	Cu
UL factory wiring	✓
UL field wiring	✓


1393.5

TRK 1,5/15/STB BU

TRK 1,5/15/STB BU

Media

---



**M3**



**CRAUS**<sup>®</sup>

1393.5

TRK 1,5/15/STB BU

TRK 1,5/15/STB BU

## Accessories

---

### External insulated cross-connector

---



External insulated cross-connector, No. of poles: 2,  
Mounting type: Plug in, Width: 10.8 mm, Rated  
current: 27 A; Colour: Yellow

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2064.0	AQI 2/6/17	4044211048709	50 PC

---



External insulated cross-connector, No. of poles: 3,  
Mounting type: Plug in, Width: 16.9 mm, Rated  
current: 27 A; Colour: Yellow

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2065.0	AQI 3/6/17	4044211048716	50 PC

---



1393.5

TRK 1,5/15/STB BU


TRK 1,5/15/STB BU

## Accessories

---

### External insulated cross-connector

---



External insulated cross-connector, No. of poles: 4, Mounting type: Plug in, Width: 23 mm, Rated current: 27 A; Colour: Yellow

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2066.0	AQI 4/6/17	4044211048723	50 PC

---

### End bracket

---



End stop, Mounting type: Mounting rail TS 15/5.5, Width: 7.5 mm, Colour: Beige

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2074.2	ES 15	4044211048822	50 PC

---

1393.5

TRK 1,5/15/STB BU

TRK 1,5/15/STB BU

## Accessories

---

### Test plug

---



Test plug, Colour: Red


### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
2007.0	PS 2,3	4044211048105	20 PC

---

### Quick-marking

---



Terminal marker / Pocket Maxicard, Length: 5 mm,  
Width: 8 mm, Colour: White

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
9323.7	PMC SB 8/40 WH	4044211129231	400 PC

---

1393.5

TRK 1,5/15/STB BU

TRK 1,5/15/STB BU

## Accessories

---

### Screw driver

---



Screwdriver with bare blade, Colour: Black-grey

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1086.0	SDB 0,6x3,5	4044211014797	1 PC

---