


1441.2

SL 16/35 Ex GNYE

SL 16/35 Ex GNYE



Ex protective-earth terminal ATEX-certified Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 16 mm<sup>2</sup>, Width: 12 mm, Colour: Green-yellow

## Business data

Product description	Ex protective earthing terminal ATEX-certified
Explosion-proof version (EEx e)	✓
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	53
Weight per piece (including packaging)	54.8
Unit of weight	G
Customs number	85369010
Country of origin	DE

1441.2

SL 16/35 Ex GNYE

SL 16/35 Ex GNYE

## Technical Data

---

### Dimensions

---

Length	50 mm
Width	12 mm
Height TS 35/7.5	63 mm

### Ratings

---

Rated cross-section	16 mm <sup>2</sup>
Overvoltage category	III
Contamination degree	3

1441.2

SL 16/35 Ex GNYE

SL 16/35 Ex GNYE

## Technical Data

---

### Connection data

Connection principle	Screw connection
Connection position	Lateral
Connections	2
Number of terminals per level	2
Number of levels	1
Wire cross-section single-core (rigid) / stranded, min.	2.5 mm <sup>2</sup>
Wire cross-section single core (rigid)/stranded, max.	16 mm <sup>2</sup>
Wire cross-section stranded, min.	2.5 mm <sup>2</sup>
Wire cross-section stranded, max.	16 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, min.	2.5 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, max.	16 mm <sup>2</sup>
Wire cross-section AWG, min.	10
Wire cross-section AWG, max.	4
Stripping length	15 mm
Screw head	Slotted
Screw threading	M 5
Tightening torque, min.	2 Nm
Tightening torque, max.	4 Nm

1441.2

SL 16/35 Ex GNYE

SL 16/35 Ex GNYE

## Technical Data

---

### Materials

---

Insulation housing	Polyamide 6.6
--------------------	---------------

Flammability class UL 94	V-2
--------------------------	-----

Working temperature, min.	-40 °C
---------------------------	--------

Working temperature, max.	105 °C
---------------------------	--------

### Further technical data

---

Mounting type	Mounting rail TS 35/7,5
---------------	-------------------------

Gauge plug acc. to EN 60 947-1	B7
--------------------------------	----

1441.2

SL 16/35 Ex GNYE

SL 16/35 Ex GNYE

## Approvals

---

### Standards and regulations

---

Partial certification number	NEMKO ATEX 1136 U
------------------------------	-------------------

EAC approval	TR ZU 004/2011
--------------	----------------

EAC approval granted	✓
----------------------	---

Nemko approval	EN 60947-7-2
----------------	--------------

Nemko approval granted	✓
------------------------	---

### CSA approval

---

CSA approval	C22.2 No 158
--------------	--------------

CSA approval granted	✓
----------------------	---

CSA wire cross-section AWG, min.	12
----------------------------------	----

CSA wire cross-section AWG, max.	6
----------------------------------	---

CSA stripping length	15 mm
----------------------	-------

### CSAus approval

---

CSAus approval	UL 1059
----------------	---------

CSAus approval granted	✓
------------------------	---

CSAus wire cross-section AWG, min.	12
------------------------------------	----

CSAus wire cross-section AWG, max.	6
------------------------------------	---

1441.2

SL 16/35 Ex GNYE

SL 16/35 Ex GNYE

## Approvals

---

### CSAus approval

---

CSAus stripping length	15 mm
------------------------	-------

---

### cUL Recognized

---

cUL Recognized	C22.2 No 158
----------------	--------------

---

cUL Recognized	✓
----------------	---

---

cUL wire cross-section single-core (rigid) AWG, min.	10
--	----

---

cUL wire cross-section single-core (rigid) AWG, max.	4
--	---

---

cUL wire cross-section stranded AWG, min.	10
---	----

---

cUL wire cross-section stranded AWG, max.	4
---	---

---

cUL torque	20 Nm
------------	-------

---

cUL wire material	Cu
-------------------	----

---

### KEMA KEUR approval

---

KEMA KEUR approval	EN 60947-7-2
--------------------	--------------

---

KEMA KEUR approval granted	✓
----------------------------	---

---

KEMA wire cross-section single core (rigid), min.	1.5 mm <sup>2</sup>
---	---------------------

---

KEMA wire cross-section single-core (rigid), max.	25 mm <sup>2</sup>
---	--------------------

---

KEMA wire cross-section stranded, min.	1.5 mm <sup>2</sup>
--	---------------------

---

1441.2

SL 16/35 Ex GNYE

SL 16/35 Ex GNYE

## Approvals

---

### KEMA KEUR approval

---

KEMA wire cross-section stranded, max.	16 mm <sup>2</sup>
--	--------------------

---

### UL Recognized

---

UL Recognized	UL 1059
---------------	---------

---

UL Recognized granted	✓
-----------------------	---

---

UL wire cross-section single-core (rigid) AWG, min.	10
---	----

---

UL wire cross-section single-core (rigid) AWG, max.	4
---	---

---

UL wire cross-section stranded AWG, min.	10
--	----

---

UL wire cross-section stranded AWG, max.	4
--	---

---

UL torque	20 Lb In
-----------	----------

---

UL wire material	Cu
------------------	----

---

UL factory wiring	✓
-------------------	---

---

UL field wiring	✓
-----------------	---

---


1441.2

SL 16/35 Ex GNYE


SL 16/35 Ex GNYE

## Media

---



**M5**



**EAC**



1441.2

SL 16/35 Ex GNYE

SL 16/35 Ex GNYE

Media

---



1441.2

SL 16/35 Ex GNYE


SL 16/35 Ex GNYE

## Accessories

---

### Quick-marking

---



Terminal marker / Pocket Maxicard, Length: 5 mm,  
Width: 6 mm, Colour: White

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
4702.7	PMC SB 6/50 WH	4044211089986	500 PC

---

### Screw driver

---



Screwdriver with bare blade, Colour: Black-grey

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1087.0	SDB 0,8x4,0	4044211014803	1 PC

---