


15300.2 SD-S25C SD-S25C



Interface module for D-SUB, Screw connection and male D-SUB plug-in connector, Mounting type: Mounting rail TS 35, No. of poles: 25

Business data

Product description	Interface module
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	106.6
Weight per piece (including packaging)	139.3
Unit of weight	G
Customs number	85369010
Country of origin	EEC

15300.2 SD-S25C SD-S25C

Technical Data

Dimensions

Length	47 mm
Width	78 mm
Height TS 35/7.5	61 mm

Ratings

Overvoltage category	III
Contamination degree	2

Connection data

Connection principle	Screw connection
Number of connections	1
No. of poles	25
Wire cross-section single core (rigid), min.	0.2 mm ²
Wire cross-section single-core (rigid), max.	4 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	2.5 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm ²
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm ²

15300.2 SD-S25C SD-S25C

Technical Data

Connection data

Stripping length	7 mm
Torque	0.6 Nm

Input data

Max. operating voltage AC/DC	125 V
Current load per channel, max.	1,5 A

Materials

Working temperature, min.	-20 °C
Working temperature, max.	50 °C

Further technical data

Connector type	D-sub male plug
Test voltage	0.67 kV
Shielded	✓

15300.2
SD-S25C
SD-S25C

Approvals

Standards and regulations

Standards / specifications

DIN VDE 0110 / EN 50178

15300.2
SD-S25C
SD-S25C

Media

