



15301.2

SD-S 25CZ

SD-S 25CZ



Interface module for D-SUB, Tension-spring connection and male D-SUB plug-in connector, Mounting type: Mounting rail TS 35, No. of poles: 25

Business data

Product description	Interface module
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	66.5
Weight per piece (including packaging)	129.9
Unit of weight	G
Customs number	85369010
Country of origin	EEC

15301.2

SD-S 25CZ

SD-S 25CZ

Technical Data

Dimensions

Length	47 mm
Width	78 mm
Height TS 35/7.5	38 mm

Ratings

Overvoltage category	III
Contamination degree	2

Connection data

Connection principle	Tension-spring connection
Number of connections	1
No. of poles	25
Wire cross-section single core (rigid), min.	0.08 mm ²
Wire cross-section single-core (rigid), max.	2.5 mm ²
Wire cross-section stranded, min.	0.14 mm ²
Wire cross-section stranded, max.	2.5 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.14 mm ²
Wire cross-section stranded with wire-end ferrules, max.	1.5 mm ²

15301.2

SD-S 25CZ

SD-S 25CZ

Technical Data

Connection data

Stripping length	6 mm
------------------	------

Input data

Max. operating voltage AC/DC	125 V
------------------------------	-------

Current load per channel, max.	1,5 A
--------------------------------	-------

Materials

Working temperature, min.	-20 °C
---------------------------	--------

Working temperature, max.	50 °C
---------------------------	-------

Further technical data

Connector type	D-sub male plug
----------------	-----------------

Test voltage	0.67 kV
--------------	---------

Shielded	✓
----------	---

15301.2

SD-S 25CZ

SD-S 25CZ

Approvals

Standards and regulations

Standards / specifications

DIN VDE 0110 / EN 50178

15301.2

SD-S 25CZ

SD-S 25CZ

Media

