

1536.2

SL 16/35/N/IS GNYE

SL 16/35/N/IS GNYE



Protective earth terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 35 mm<sup>2</sup>, Width: 12 mm, Colour: Green-yellow

## Business data

Product description	Protective earth terminal
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	52.48
Weight per piece (including packaging)	54.4
Unit of weight	G
Customs number	85369010
Country of origin	DE

**1536.2**

**SL 16/35/N/IS GNYE**

**SL 16/35/N/IS GNYE**

## Technical Data

---

### Dimensions

---

Length	50 mm
Width	12 mm
Height TS 35/7.5	53 mm

### Ratings

---

Rated cross-section	35 mm <sup>2</sup>
Overvoltage category	III
Contamination degree	3

**1536.2**

**SL 16/35/N/IS GNYE**

**SL 16/35/N/IS GNYE**

## Technical Data

---

### Connection data

Connection principle	Screw connection
Connection position	Lateral
Connections	2
Number of terminals per level	2
Number of levels	1
Wire cross-section single-core (rigid) / stranded, min.	2.5 mm <sup>2</sup>
Wire cross-section single core (rigid)/stranded, max.	25 mm <sup>2</sup>
Wire cross-section stranded, min.	2.5 mm <sup>2</sup>
Wire cross-section stranded, max.	16 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, min.	2.5 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, max.	16 mm <sup>2</sup>
Wire cross-section AWG, min.	10
Wire cross-section AWG, max.	4
Stripping length	15 mm
Screw head	Inner hex (Allen)
Screw threading	M 5
Tightening torque, min.	2 Nm
Tightening torque, max.	4 Nm

1536.2

SL 16/35/N/IS GNYE

SL 16/35/N/IS GNYE

## Technical Data

---

### Materials

---

Insulation housing	Polyamide 6.6
--------------------	---------------

Flammability class UL 94	V-2
--------------------------	-----

Working temperature, min.	-40 °C
---------------------------	--------

Working temperature, max.	105 °C
---------------------------	--------

### Further technical data

---

Mounting type	Mounting rail TS 35/7,5
---------------	-------------------------

Gauge plug acc. to EN 60 947-1	B7
--------------------------------	----

Number of cross-connection channels	1
-------------------------------------	---

1536.2

SL 16/35/N/IS GNYE

SL 16/35/N/IS GNYE

## Approvals

---

### Standards and regulations

---

EAC approval	TR ZU 004/2013
--------------	----------------

EAC approval granted	✓
----------------------	---

### CSA approval

---

CSA approval	C22.2 No 158
--------------	--------------

CSA approval granted	✓
----------------------	---

CSA wire cross-section AWG, min.	12
----------------------------------	----

CSA wire cross-section AWG, max.	6
----------------------------------	---

CSA stripping length	15 mm
----------------------	-------

### CSAus approval

---

CSAus approval	UL 1059
----------------	---------

CSAus approval granted	✓
------------------------	---

CSAus wire cross-section AWG, min.	12
------------------------------------	----

CSAus wire cross-section AWG, max.	6
------------------------------------	---

CSAus stripping length	15 mm
------------------------	-------

1536.2

SL 16/35/N/IS GNYE

SL 16/35/N/IS GNYE

## Approvals

---

### KEMA KEUR approval

KEMA KEUR approval	EN 60947-7-2
KEMA KEUR approval granted	✓
KEMA wire cross-section single core (rigid), min.	1.5 mm <sup>2</sup>
KEMA wire cross-section single-core (rigid), max.	25 mm <sup>2</sup>
KEMA wire cross-section stranded, min.	1.5 mm <sup>2</sup>
KEMA wire cross-section stranded, max.	16 mm <sup>2</sup>



1536.2

SL 16/35/N/IS GNYE

SL 16/35/N/IS GNYE

## Media

---



**M5**



**EAC**



1536.2

SL 16/35/N/IS GNYE


SL 16/35/N/IS GNYE

## Accessories

---

### Quick-marking

---



Terminal marker / Pocket Maxicard, Length: 5 mm,  
Width: 6 mm, Colour: White

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
4702.7	PMC SB 6/50 WH	4044211089986	500 PC

### Screw driver

---



Screwdriver with bare blade, Colour: Black-grey

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1087.0	SDB 0,8x4,0	4044211014803	1 PC