

15904.2 RJS45-SH RJS45-SH



Interface module for RJ45, Shielded, CAT 5, Push-In connection and RJ45 plug-in connector, Mounting type: Mounting rail TS 35, No. of poles: 9

Business data

Product description	Interface module
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	47.2
Weight per piece (including packaging)	61.05
Unit of weight	G
Customs number	85369010
Country of origin	EEC

15904.2 RJS45-SH RJS45-SH

Technical Data

Dimensions

Length	87 mm
Width	26 mm
Height TS 35/7.5	63 mm

Ratings

Overvoltage category	III
Contamination degree	2

Connection data

Connection principle	Push-in connection
Number of connections	1
No. of poles	8
Wire cross-section single core (rigid), min.	0.05 mm ²
Wire cross-section single-core (rigid), max.	1.5 mm ²
Wire cross-section stranded, min.	0.14 mm ²
Wire cross-section stranded, max.	1 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.14 mm ²
Wire cross-section stranded with wire-end ferrules, max.	0.5 mm ²

15904.2 RJS45-SH RJS45-SH

Technical Data

Connection data

Stripping length	9 mm
------------------	------

Input data

Max. operating voltage AC/DC	125 V
------------------------------	-------

Current load per channel, max.	1 A
--------------------------------	-----

Output data

Contact material	Phosphor bronze 1.27 μ m Au over 1.27 μ m Ni
------------------	--

Materials

Working temperature, min.	-20 °C
---------------------------	--------

Working temperature, max.	50 °C
---------------------------	-------

15904.2
RJS45-SH
RJS45-SH

Technical Data

Further technical data

Connector type	RJ45
Plug-in cycles acc. to standard	750
Test voltage	0.75 kV
Shielded	✓
Category	CAT 5

15904.2

RJS45-SH

RJS45-SH

Approvals

Standards and regulations

Standards / specifications

DIN VDE 0110 / EN 50178

15904.2

RJS45-SH

RJS45-SH

Media

