

17008.0

QS 2/16

QS 2/16



Cross-connector, No. of poles: 2, Mounting type: Can be screwed on, Width: 27 mm, Rated cross-section: 16 mm², Colour: natural

Business data

| | |
|--|-----------------|
| Product description | Cross-connector |
| Packaging unit | 10 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 9.6 |
| Weight per piece (including packaging) | 9.8 |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | DE |

17008.0

QS 2/16

QS 2/16

Technical Data

Dimensions

| | |
|---------------------------------------|--------|
| Length | 12 mm |
| Width | 27 mm |
| Height | 4 mm |
| Hole diameter | 5.6 mm |
| Hole spacing (mid-point to mid-point) | 15 mm |
| Pitch size | 15 mm |

Ratings

| | |
|----------------------|--------------------|
| Max. voltage | 1000 V |
| Rated current | 76 A |
| Rated cross-section | 16 mm ² |
| Contamination degree | 3 |

Connection data

| | |
|--------------|---|
| No. of poles | 2 |
|--------------|---|

Materials

| | |
|----------|--------|
| Material | Copper |
|----------|--------|

17008.0

QS 2/16

QS 2/16

Technical Data

Materials

| | |
|---------|------------|
| Surface | Tin-plated |
|---------|------------|

Further technical data

| | |
|---------------|-----------|
| Mounting type | Screwable |
|---------------|-----------|

| | |
|-----------------------------|---|
| Number of bridged terminals | 2 |
|-----------------------------|---|
