

17209.8

SQI 2,5/10 YE

SQI 2,5/10 YE

---



Insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 50.7 mm, Rated cross-section: 2.5 mm<sup>2</sup>, Colour: Yellow

## Business data

---

Product description	Insulated cross-connector
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	5.6
Weight per piece (including packaging)	5.74
Unit of weight	G
Customs number	85389099
Country of origin	DE

**17209.8**

**SQI 2,5/10 YE**

**SQI 2,5/10 YE**

## Technical Data

---

### Dimensions

---

Length	4 mm
Width	50.7 mm
Pitch size	5 mm

### Ratings

---

Voltage with partition, max.	1000 V
Voltage without partition, max.	1000 V
Rated current	24 A
Current load, max.	32 A
Rated cross-section	2.5 mm <sup>2</sup>
Contamination degree	3

### Connection data

---

No. of poles	10
--------------	----

17209.8

SQI 2,5/10 YE

SQI 2,5/10 YE

## Technical Data

---

### Materials

Material	Bronze
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

### Further technical data

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	10

17209.8

SQI 2,5/10 YE

SQI 2,5/10 YE

## Accessories

---

### Insulating cover for cross-connector

---



Insulating cap, Colour: Yellow

---

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
17200.8	SQIK 2,5-10	4044211148539	20 PC

---