

17218.8

SQI 4/9 YE

SQI 4/9 YE



Insulated cross-connector, No. of poles: 9, Mounting type: Plug in, Width: 54 mm, Rated cross-section: 4 mm², Colour: Yellow

Business data

| | |
|--|---------------------------|
| Product description | Insulated cross-connector |
| Packaging unit | 10 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 6.5 |
| Weight per piece (including packaging) | 6.6 |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | DE |

17218.8

SQI 4/9 YE

SQI 4/9 YE

Technical Data

Dimensions

| | |
|------------|-------|
| Length | 4 mm |
| Width | 54 mm |
| Pitch size | 6 mm |

Ratings

| | |
|---------------------------------|-------------------|
| Voltage with partition, max. | 1000 V |
| Voltage without partition, max. | 1000 V |
| Rated current | 32 A |
| Current load, max. | 41 A |
| Rated cross-section | 4 mm ² |
| Contamination degree | 3 |

Connection data

| | |
|--------------|---|
| No. of poles | 9 |
|--------------|---|

17218.8

SQI 4/9 YE

SQI 4/9 YE

Technical Data

Materials

| | |
|---------------------------|---------------|
| Material | Bronze |
| Insulation housing | Polyamide 6.6 |
| Flammability class UL 94 | V-2 |
| Working temperature, min. | -40 °C |
| Working temperature, max. | 105 °C |

Further technical data

| | |
|-------------------------------|---------|
| Mounting type | Plug in |
| Insulation available | ✓ |
| Touch protection is available | ✓ |
| Number of bridged terminals | 9 |

17218.8

SQI 4/9 YE

SQI 4/9 YE

Accessories

Insulating cover for cross-connector



Insulating cap, Colour: Yellow

In general

| Order number | Article designation | GTIN (EAN) | Packaging unit |
|--------------|---------------------|---------------|----------------|
| 17200.8 | SQIK 2,5-10 | 4044211148539 | 20 PC |
