

17220.8

SQI 4/30 YE

SQI 4/30 YE

---



Insulated cross-connector, No. of poles: 30, Mounting type: Plug in, Width: 181.1 mm, Rated cross-section: 4 mm<sup>2</sup>, Colour: Yellow

## Business data

---

Product description	Insulated cross-connector
Packaging unit	5
Quantity unit	PC
Weight per piece (not including packaging)	21
Weight per piece (including packaging)	22
Unit of weight	G
Customs number	85389099
Country of origin	DE

---

**17220.8**

**SQI 4/30 YE**

**SQI 4/30 YE**

## Technical Data

---

### Dimensions

---

Length	4.2 mm
--------	--------

Width	181.1 mm
-------	----------

Pitch size	6 mm
------------	------

### Ratings

---

Voltage with partition, max.	1000 V
------------------------------	--------

Voltage without partition, max.	1000 V
---------------------------------	--------

Rated current	32 A
---------------	------

Current load, max.	41 A
--------------------	------

Rated cross-section	4 mm <sup>2</sup>
---------------------	-------------------

Contamination degree	3
----------------------	---

### Connection data

---

No. of poles	30
--------------	----

17220.8

SQI 4/30 YE

SQI 4/30 YE

## Technical Data

---

### Materials

Material	Bronze
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

### Further technical data

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	30

17220.8

SQI 4/30 YE

SQI 4/30 YE

## Accessories

---

### Insulating cover for cross-connector

---



Insulating cap, Colour: Yellow

---

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
17200.8	SQIK 2,5-10	4044211148539	20 PC

---