

2741.2

QI 3 YE

QI 3 YE



M3 

Insulated cross-connector, No. of poles: 3, Mounting type: Can be screwed on, Width: 16.5 mm, Colour: Yellow

## Business data

Product description	Insulated cross-connector
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	5.22
Weight per piece (including packaging)	5.28
Unit of weight	G
Customs number	85389099
Country of origin	DE

2741.2

QI 3 YE

QI 3 YE

## Technical Data

---

### Dimensions

---

Length	2.3 mm
Width	16.5 mm
Pitch size	6 mm

### Ratings

---

Voltage with partition, max.	800 V
Voltage without partition, max.	400 V
Rated current	32 A
Contamination degree	3

### Connection data

---

No. of poles	3
Screw head	Slotted
Screw threading	M 3
Tightening torque, min.	0.5 Nm
Tightening torque, max.	1 Nm

2741.2

QI 3 YE

QI 3 YE

## Technical Data

---

### Materials

---

Material	Copper
Surface	Tin-plated
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

### Further technical data

---

Mounting type	Screwable
Insulation available	✓
Number of bridged terminals	3

2741.2

QI 3 YE

QI 3 YE

Media

---

**M3**



2741.2  
QI 3 YE  
QI 3 YE

## Accessories

---

### Screw driver

---



Screwdriver with bare blade, Colour: Black-grey

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1086.0	SDB 0,6x3,5	4044211014797	1 PC

---