

2751.2

QI 3 YE

QI 3 YE



Insulated cross-connector, No. of poles: 3, Mounting type: Can be screwed on, Width: 21.7 mm, Colour: Yellow

Business data

| | |
|--|---------------------------|
| Product description | Insulated cross-connector |
| Packaging unit | 50 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 6.96 |
| Weight per piece (including packaging) | 6.99 |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | DE |

2751.2
QI 3 YE
QI 3 YE

Technical Data

Dimensions

| | |
|------------|---------|
| Length | 2.4 mm |
| Width | 21.7 mm |
| Pitch size | 8 mm |

Ratings

| | |
|---------------------------------|-------|
| Voltage with partition, max. | 800 V |
| Voltage without partition, max. | 400 V |
| Rated current | 57 A |
| Contamination degree | 3 |

Connection data

| | |
|-------------------------|---------|
| No. of poles | 3 |
| Screw head | Slotted |
| Screw threading | M 3 |
| Tightening torque, min. | 0.5 Nm |
| Tightening torque, max. | 1 Nm |

2751.2

QI 3 YE

QI 3 YE

Technical Data

Materials

| | |
|---------------------------|---------------|
| Material | Copper |
| Surface | Tin-plated |
| Insulation housing | Polyamide 6.6 |
| Flammability class UL 94 | V-2 |
| Working temperature, min. | -40 °C |
| Working temperature, max. | 105 °C |

Further technical data

| | |
|-----------------------------|-----------|
| Mounting type | Screwable |
| Insulation available | ✓ |
| Number of bridged terminals | 3 |

2751.2

QI 3 YE

QI 3 YE

Media

M3



2751.2
QI 3 YE
QI 3 YE

Accessories

Screw driver



Screwdriver with bare blade, Colour: Black-grey

In general

| Order number | Article designation | GTIN (EAN) | Packaging unit |
|--------------|---------------------|---------------|----------------|
| 1086.0 | SDB 0,6x3,5 | 4044211014797 | 1 PC |
