

2794.0

HZL/0,5-D WH

HZL/0,5-D WH

---



Wire-end ferrules, Max. wire cross-section: 0.5 mm<sup>2</sup>, Length: 14 mm, Length of copper pipe: 8 mm, Colour: White

## Business data

---

|  |          |
|--|----------|
| Product description                        | Ferrules |
| Packaging unit                             | 500      |
| Quantity unit                              | PC       |
| Weight per piece (not including packaging) | 0.11     |
| Weight per piece (including packaging)     | 0.12     |
| Unit of weight                             | G        |
| Customs number                             | 85369010 |
| Country of origin                          | DE       |

2794.0

HZL/0,5-D WH

HZL/0,5-D WH

## Technical Data

---

### Dimensions

---

|                                  |         |
|----------------------------------|---------|
| Length                           | 14 mm   |
| Length of copper pipe            | 8 mm    |
| Width of plastic collar          | 3 mm    |
| Height of plastic collar         | 5 mm    |
| Diameter of copper pipe          | 1.4 mm  |
| Wall thickness of copper pipe    | 0.15 mm |
| Wall thickness of plastic collar | 0.3 mm  |

### Connection data

---

|                              |                     |
|------------------------------|---------------------|
| Wire cross-section, max.     | 0.5 mm <sup>2</sup> |
| Wire cross-section AWG, max. | 20                  |
| Stripping length             | 11 mm               |
| 2-wire plastic collar        | ✓                   |

### Materials

---

|                |                                |
|----------------|--------------------------------|
| Copper pipe    | Copper alloy                   |
| Surface        | Galvanically tin-plated, shiny |
| Plastic collar | Polypropylene homopolymer      |

2794.0

HZL/0,5-D WH

HZL/0,5-D WH

## Technical Data

---

### Materials

---

|                           |        |
|---------------------------|--------|
| Working temperature, min. | -5 °C  |
| Working temperature, max. | 105 °C |

---

### Further technical data

---

|                      |   |
|----------------------|---|
| Insulation available | ✓ |
|----------------------|---|

---

# Datasheet



2794.0

HZL/0,5-D WH

HZL/0,5-D WH

## Approvals

---

## Standards and regulations

---

DIN 46228-4:1990

✓