

2796.0

HZL/1,0 HL-D RD

HZL/1,0 HL-D RD

---



Wire-end ferrules, Max. wire cross-section: 1 mm<sup>2</sup>, Length: 19 mm, Length of copper pipe: 12 mm, Colour: Red

## Business data

---

Product description	Ferrules
Packaging unit	500
Quantity unit	PC
Weight per piece (not including packaging)	0.17
Weight per piece (including packaging)	0.18
Unit of weight	G
Customs number	85369010
Country of origin	DE

2796.0

HZL/1,0 HL-D RD

HZL/1,0 HL-D RD

## Technical Data

---

### Dimensions

---

Length	19 mm
Length of copper pipe	12 mm
Width of plastic collar	3.2 mm
Height of plastic collar	5.8 mm
Diameter of copper pipe	2 mm
Wall thickness of copper pipe	0.15 mm
Wall thickness of plastic collar	0.3 mm

### Connection data

---

Wire cross-section, max.	1 mm <sup>2</sup>
Wire cross-section AWG, max.	17
Stripping length	16 mm
2-wire plastic collar	✓

### Materials

---

Copper pipe	Copper alloy
Surface	Galvanically tin-plated, shiny
Plastic collar	Polypropylene homopolymer

2796.0

HZL/1,0 HL-D RD

HZL/1,0 HL-D RD

## Technical Data

---

### Materials

---

Working temperature, min.	-5 °C
Working temperature, max.	105 °C

---

### Further technical data

---

Insulation available	✓
----------------------	---

---

2796.0

HZL/1,0 HL-D RD

HZL/1,0 HL-D RD

## Approvals

---

## Standards and regulations

---

DIN 46228-4:1990

✓