

2802.0

HZL/16,0-D BU

HZL/16,0-D BU



Wire-end ferrules, Max. wire cross-section: 16 mm², Length: 29 mm, Length of copper pipe: 16 mm, Colour: Blue

Business data

| | |
|--|----------|
| Product description | Ferrules |
| Packaging unit | 50 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 1.35 |
| Weight per piece (including packaging) | 1.36 |
| Unit of weight | G |
| Customs number | 85369010 |
| Country of origin | DE |

2802.0

HZL/16,0-D BU

HZL/16,0-D BU

Technical Data

Dimensions

| | |
|----------------------------------|---------|
| Length | 29 mm |
| Length of copper pipe | 16 mm |
| Width of plastic collar | 9.5 mm |
| Height of plastic collar | 17.2 mm |
| Diameter of copper pipe | 8.3 mm |
| Wall thickness of copper pipe | 0.3 mm |
| Wall thickness of plastic collar | 0.6 mm |

Connection data

| | |
|------------------------------|--------------------|
| Wire cross-section, max. | 16 mm ² |
| Wire cross-section AWG, max. | 6 |
| Stripping length | 20 mm |
| 2-wire plastic collar | ✓ |

Materials

| | |
|----------------|--------------------------------|
| Copper pipe | Copper alloy |
| Surface | Galvanically tin-plated, shiny |
| Plastic collar | Polypropylene homopolymer |

2802.0

HZL/16,0-D BU

HZL/16,0-D BU

Technical Data

Materials

| | |
|---------------------------|--------|
| Working temperature, min. | -5 °C |
| Working temperature, max. | 105 °C |

Further technical data

| | |
|----------------------|---|
| Insulation available | ✓ |
|----------------------|---|

2802.0

HZL/16,0-D BU

HZL/16,0-D BU

Approvals

Standards and regulations

DIN 46228-4:1990

✓