

2859.0

H 35,0/30-D RD

H 35,0/30-D RD



Wire-end ferrules, Max. wire cross-section: 35 mm², Length: 30 mm, Length of copper pipe: 16 mm, Colour: Red

Business data

Product description	Ferrules
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	1.74
Weight per piece (including packaging)	1.75
Unit of weight	G
Customs number	85369010
Country of origin	DE

2859.0

H 35,0/30-D RD

H 35,0/30-D RD

Technical Data

Dimensions

Length	30 mm
Length of copper pipe	16 mm
Diameter of copper pipe	8.3 mm
Diameter plastic collar	12.7 mm
Wall thickness of copper pipe	0.2 mm
Wall thickness of plastic collar	0.4 mm

Connection data

Wire cross-section, max.	35 mm ²
Wire cross-section AWG, max.	2
Stripping length	19 mm

Materials

Copper pipe	Copper alloy
Surface	Galvanically tin-plated, shiny
Plastic collar	Polypropylene homopolymer
Working temperature, min.	-5 °C
Working temperature, max.	105 °C

Further technical data

Insulation available	✓
----------------------	---

Datasheet



2859.0

H 35,0/30-D RD

H 35,0/30-D RD

Approvals

Standards and regulations

DIN 46228-4:1990

✓