

3041.0

HZL 4,0-T OG

HZL 4,0-T OG



Wire-end ferrules, Max. wire cross-section: 4 mm², Length: 22 mm, Length of copper pipe: 12 mm, Colour: Orange

Business data

| | |
|--|----------|
| Product description | Ferrules |
| Packaging unit | 100 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 0.47 |
| Weight per piece (including packaging) | 0.48 |
| Unit of weight | G |
| Customs number | 85369010 |
| Country of origin | DE |

3041.0

HZL 4,0-T OG

HZL 4,0-T OG

Technical Data

Dimensions

| | |
|----------------------------------|--------|
| Length | 22 mm |
| Length of copper pipe | 12 mm |
| Width of plastic collar | 5.2 mm |
| Height of plastic collar | 9 mm |
| Diameter of copper pipe | 3.5 mm |
| Wall thickness of copper pipe | 0.2 mm |
| Wall thickness of plastic collar | 0.5 mm |

Connection data

| | |
|------------------------------|-------------------|
| Wire cross-section, max. | 4 mm ² |
| Wire cross-section AWG, max. | 12 |
| Stripping length | 15 mm |
| 2-wire plastic collar | ✓ |

Materials

| | |
|----------------|--------------------------------|
| Copper pipe | Copper alloy |
| Surface | Galvanically tin-plated, shiny |
| Plastic collar | Polypropylene homopolymer |

3041.0

HZL 4,0-T OG

HZL 4,0-T OG

Technical Data

Materials

| | |
|---------------------------|--------|
| Working temperature, min. | -5 °C |
| Working temperature, max. | 105 °C |

Further technical data

| | |
|----------------------|---|
| Insulation available | ✓ |
|----------------------|---|

3041.0

HZL 4,0-T OG

HZL 4,0-T OG

Approvals

Standards and regulations

DIN 46228-4:1990

✓