

3042.0

HZL 4,0 L-T OG

HZL 4,0 L-T OG



Wire-end ferrules, Max. wire cross-section: 4 mm², Length: 28 mm, Length of copper pipe: 18 mm, Colour: Orange

Business data

Product description	Ferrules
Packaging unit	100
Quantity unit	PC
Weight per piece (not including packaging)	0.21
Weight per piece (including packaging)	0.23
Unit of weight	G
Customs number	85369010
Country of origin	EEC

3042.0

HZL 4,0 L-T OG

HZL 4,0 L-T OG

Technical Data

Dimensions

Length	28 mm
Length of copper pipe	18 mm
Width of plastic collar	5.2 mm
Height of plastic collar	9 mm
Diameter of copper pipe	3.5 mm
Wall thickness of copper pipe	0.2 mm
Wall thickness of plastic collar	0.5 mm

Connection data

Wire cross-section, max.	4 mm ²
Wire cross-section AWG, max.	12
Stripping length	21 mm
2-wire plastic collar	✓

Materials

Copper pipe	Copper alloy
Surface	Galvanically tin-plated, shiny
Plastic collar	Polypropylene homopolymer

3042.0

HZL 4,0 L-T OG

HZL 4,0 L-T OG

Technical Data

Materials

Working temperature, min.	-5 °C
Working temperature, max.	105 °C

Further technical data

Insulation available	✓
----------------------	---

3042.0

HZL 4,0 L-T OG

HZL 4,0 L-T OG

Approvals

Standards and regulations

DIN 46228-4:1990

✓