

3048.0

HZL 16,0 L-T WH

HZL 16,0 L-T WH



Wire-end ferrules, Max. wire cross-section: 16 mm², Length: 38 mm, Length of copper pipe: 25 mm, Colour: White

Business data

Product description	Ferrules
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	0.21
Weight per piece (including packaging)	0.22
Unit of weight	G
Customs number	85369010
Country of origin	EEC

3048.0

HZL 16,0 L-T WH

HZL 16,0 L-T WH

Technical Data

Dimensions

Length	38 mm
Length of copper pipe	25 mm
Width of plastic collar	9.5 mm
Height of plastic collar	17.2 mm
Diameter of copper pipe	8.3 mm
Wall thickness of copper pipe	0.3 mm
Wall thickness of plastic collar	0.6 mm

Connection data

Wire cross-section, max.	16 mm ²
Wire cross-section AWG, max.	6
Stripping length	29 mm
2-wire plastic collar	✓

Materials

Copper pipe	Copper alloy
Surface	Galvanically tin-plated, shiny
Plastic collar	Polypropylene homopolymer

3048.0

HZL 16,0 L-T WH

HZL 16,0 L-T WH

Technical Data

Materials

Working temperature, min.	-5 °C
Working temperature, max.	105 °C

Further technical data

Insulation available	✓
----------------------	---

3048.0

HZL 16,0 L-T WH

HZL 16,0 L-T WH

Approvals

Standards and regulations

DIN 46228-4:1990

✓