

3082.0

H 1,5/17,5 KS BK

H 1,5/17,5 KS BK



Wire-end ferrules, Max. wire cross-section: 1.5 mm², Length: 17.5 mm, Length of copper pipe: 8 mm, Colour: Black

Business data

Product description	Ferrules
Packaging unit	100
Quantity unit	PC
Weight per piece (not including packaging)	0.25
Weight per piece (including packaging)	0.26
Unit of weight	G
Customs number	85369010
Country of origin	EEC

3082.0

H 1,5/17,5 KS BK

H 1,5/17,5 KS BK

Technical Data

Dimensions

Length	17.5 mm
Length of copper pipe	8 mm
Diameter of copper pipe	1.8 mm
Diameter plastic collar	6.4 mm
Wall thickness of copper pipe	0.15 mm
Wall thickness of plastic collar	0.3 mm

Connection data

Wire cross-section, max.	1.5 mm ²
Wire cross-section AWG, max.	16
Stripping length	8 mm

Materials

Copper pipe	Copper alloy
Surface	Galvanically tin-plated, shiny
Plastic collar	Polypropylene homopolymer
Working temperature, min.	-5 °C
Working temperature, max.	105 °C

Further technical data

Insulation available	✓
----------------------	---

3082.0

H 1,5/17,5 KS BK

H 1,5/17,5 KS BK

Approvals

Standards and regulations

DIN 46228-4:1990

✓