

3084.0

H 2,5/17,5 KS BU

H 2,5/17,5 KS BU



Wire-end ferrules, Max. wire cross-section: 2.5 mm², Length: 17.5 mm, Length of copper pipe: 8 mm, Colour: Blue

Business data

Product description	Ferrules
Packaging unit	100
Quantity unit	PC
Weight per piece (not including packaging)	0.2
Weight per piece (including packaging)	0.21
Unit of weight	G
Customs number	85369010
Country of origin	DE

3084.0

H 2,5/17,5 KS BU

H 2,5/17,5 KS BU

Technical Data

Dimensions

Length	17.5 mm
Length of copper pipe	8 mm
Diameter of copper pipe	2.3 mm
Diameter plastic collar	7.3 mm
Wall thickness of copper pipe	0.15 mm
Wall thickness of plastic collar	0.3 mm

Connection data

Wire cross-section, max.	2.5 mm ²
Wire cross-section AWG, max.	14
Stripping length	8 mm

Materials

Copper pipe	Copper alloy
Surface	Galvanically tin-plated, shiny
Plastic collar	Polypropylene homopolymer
Working temperature, min.	-5 °C
Working temperature, max.	105 °C

Further technical data

Insulation available	✓
----------------------	---

3084.0

H 2,5/17,5 KS BU

H 2,5/17,5 KS BU

Approvals

Standards and regulations

DIN 46228-4:1990

✓