

3097.0

H 0,5/10

H 0,5/10



Wire-end ferrules, Max. wire cross-section: 0.5 mm², Length: 10 mm, Colour: natural

Business data

| | |
|--|----------|
| Product description | Ferrules |
| Packaging unit | 1000 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 0.55 |
| Weight per piece (including packaging) | 0.56 |
| Unit of weight | G |
| Customs number | 85369010 |
| Country of origin | DE |

3097.0

H 0,5/10

H 0,5/10

Technical Data

Dimensions

| | |
|-------------------------------|---------|
| Length | 10 mm |
| Diameter of copper pipe | 1 mm |
| Diameter of feed-in funnel | 2.1 mm |
| Wall thickness of copper pipe | 0.15 mm |

Connection data

| | |
|------------------------------|---------------------|
| Wire cross-section, max. | 0.5 mm ² |
| Wire cross-section AWG, max. | 20 |
| Stripping length | 10 mm |

Materials

| | |
|---------------------------|--------------------------------|
| Copper pipe | Copper alloy |
| Surface | Galvanically tin-plated, shiny |
| Working temperature, max. | 120 °C |

3097.0

H 0,5/10

H 0,5/10

Approvals

Standards and regulations

DIN 46228-1:1992

✓