

3124.0

H 0,25/12-T YE

H 0,25/12-T YE



Wire-end ferrules, Max. wire cross-section: 0.75 mm², Length: 14 mm, Length of copper pipe: 8 mm, Colour: Yellow

Business data

| | |
|---------------------|----------|
| Product description | Ferrules |
|---------------------|----------|

| | |
|----------------|-----|
| Packaging unit | 500 |
|----------------|-----|

| | |
|---------------|----|
| Quantity unit | PC |
|---------------|----|

| | |
|--|------|
| Weight per piece (not including packaging) | 0.06 |
|--|------|

| | |
|--|------|
| Weight per piece (including packaging) | 0.07 |
|--|------|

| | |
|----------------|---|
| Unit of weight | G |
|----------------|---|

| | |
|----------------|----------|
| Customs number | 85369010 |
|----------------|----------|

| | |
|-------------------|----|
| Country of origin | DE |
|-------------------|----|

3124.0

H 0,25/12-T YE

H 0,25/12-T YE

Technical Data

Dimensions

| | |
|----------------------------------|---------|
| Length | 14 mm |
| Length of copper pipe | 8 mm |
| Diameter of copper pipe | 1.2 mm |
| Diameter plastic collar | 3.4 mm |
| Wall thickness of copper pipe | 0.15 mm |
| Wall thickness of plastic collar | 0.25 mm |

Connection data

| | |
|------------------------------|----------------------|
| Wire cross-section, max. | 0.75 mm ² |
| Wire cross-section AWG, max. | 18 |
| Stripping length | 10 mm |

Materials

| | |
|---------------------------|--------------------------------|
| Copper pipe | Copper alloy |
| Surface | Galvanically tin-plated, shiny |
| Plastic collar | Polypropylene homopolymer |
| Working temperature, min. | -5 °C |
| Working temperature, max. | 105 °C |

Further technical data

| | |
|----------------------|---|
| Insulation available | ✓ |
|----------------------|---|

Datasheet



3124.0

H 0,25/12-T YE

H 0,25/12-T YE

Approvals

Standards and regulations

DIN 46228-4:1990

✓