

3132.0

H 25,0/36-T BK

H 25,0/36-T BK



Wire-end ferrules, Max. wire cross-section: 25 mm², Length: 36 mm, Length of copper pipe: 22 mm, Colour: Black

Business data

Product description	Ferrules
---------------------	----------

Packaging unit	50
----------------	----

Quantity unit	PC
---------------	----

Weight per piece (not including packaging)	2.02
--	------

Weight per piece (including packaging)	2.03
--	------

Unit of weight	G
----------------	---

Customs number	85369010
----------------	----------

Country of origin	EEC
-------------------	-----

3132.0

H 25,0/36-T BK

H 25,0/36-T BK

Technical Data

Dimensions

Length	36 mm
Length of copper pipe	22 mm
Diameter of copper pipe	7.3 mm
Diameter plastic collar	11.2 mm
Wall thickness of copper pipe	0.2 mm
Wall thickness of plastic collar	0.4 mm

Connection data

Wire cross-section, max.	25 mm ²
Wire cross-section AWG, max.	4
Stripping length	24 mm

Materials

Copper pipe	Copper alloy
Surface	Galvanically tin-plated, shiny
Plastic collar	Polypropylene homopolymer
Working temperature, min.	-5 °C
Working temperature, max.	105 °C

Further technical data

Insulation available	✓
----------------------	---

3132.0

H 25,0/36-T BK

H 25,0/36-T BK

Approvals

Standards and regulations

DIN 46228-4:1990

✓